

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
		Lwr	8776			T. Penn. "B"	
T. Anhy		T. Canyon	9374	T. Ojo Alamo		T. Penn. "C"	
T. Salt		T. Strawn	10053	T. Kirtland-Fruitland		T. Penn. "D"	
B. Salt		T. Atoka	10183	T. Pictured Cliffs		T. Leadville	
T. Yates		T. Atoka LS		T. Cliff House		T. Madison	
T. 7 Rivers		T. Devonian		T. Menefee		T. Elbert	
T. Queen	1462	T. Silurian		T. Point Lookout		T. McCracken	
T. Grayburg	1788	T. Montoya		T. Mancos		T. Ignacio Qtzite	
T. San Andres	2182	T. Simpson		T. Gallup		T. Granite	
T. Glorieta		T. McKee		Base Greenhorn		T. Morrow Clastic	10535
T. Paddock		T. Ellenburger		T. Dakota		T. Lwr. Morrow	10852
T. Blinbry		T. Gr. Wash		T. Morrison		T. Austin Cycle	10868
T. Tubb		T. Granite		T. Todillo			
T. Drinkard		T. Delaware Sand		T. Entrada			
T. Abo		T. Bone Springs	3342	T. Wingate			
T. Wolfcamp	8212	T. 1st Bone Spr.	4954	T. Chinle			
T. Penn.		T. 2nd Bone Spr.	6727	T. Permian			
T. Cisco (Bough C)		T. 3rd Bone Spr.	7873	T. Penn. "A"			

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....
No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	375	375	Surface, Redbeds	6960	7860	900	Lime, Shale
375	970	595	Anhydrite, Dolomite Shale	7860	8160	300	Lime, Shale, Sand
970	1500	530	Dolomite, Anhydrite	8160	8840	680	Shale, Lime
1500	1720	220	Anhydrite, Dolomite, shale	8840	9140	300	Dolomite
1720	1815	95	Anhy, Dolomite, Sand, Shale	9140	9590	450	Dolomite, Lm. Shale, Chert
1815	2030	215	Anhydrite, Dolomite, Shale	9590	10280	690	Lime, Shale
2030	3220	1190	Dolomite	10280	10550	270	Lime, Shale, Chert
3220	3420	200	Dolomite, Chert	10550	10940	390	Shale, Lime, Sand
3420	4290	870	Lime, Chert				
4290	4960	670	Limestone				
4960	5110	150	Lime, Sand				
5110	5210	100	Shale, Lime, Sand				
5210	6270	1060	Lime				
6270	6750	480	Shale, Lime				
6750	6960	210	Shale, Lime, Sand				