

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN
(Other insti
verse side)PLICATE
ins on reForm approved.
Budget Bureau No. 48-R1484

5. LEASE DESIGNATION AND SERIAL NO.

NM 0560353

6. IF (INDIAN, ALLOTTEE, OR OTHER NAME)

7. UNIT AGENCY NAME

8. FARM OR LEASE NAME

Mabel Hale Federal

9. WELL NO.

3

10. FIELD AND TOWN, OR WELLS

Benson-Bone Spring

11. SEC., T., R., OR NEARBY
SURVEY OR AREA

Sec. 11-19S-30E

12. COUNTY & PARISH, IL. NAME

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	RECEIVED BY
2. NAME OF OPERATOR Great Western Drilling Company	OCT 16 1984
3. ADDRESS OF OPERATOR P.O. Box 1659, Midland, TX 79702	O. C. D. ARTESIA, OFFICE
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 1,980' FEL, Sec. 11, T-19-S, R-30-E (NW $\frac{1}{4}$ NE $\frac{1}{4}$) (Unit B)	
14. PERMIT NO.	15. ELEVATIONS (Show whether SW, NT, ON, etc.) 3418' G.L. (3433'KB)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDISE

REPAIR WELL

(Other)

FULL OR ALTER CASING

MULTIPLE COMPLETS

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDISING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all sections and depths pertinent to this work.)

10/3/84: T.D. 12 $\frac{1}{2}$ " hole @ 2,400' @ 11:15 a.m., 10-3-84. Ran 58 jts 8-5/8" OD, 24#/ft., K-55, ST&C, casing + float collar, guide shoe & 11 centralizers. Set csg @ 2,396'. Cemented w/800 sxs. Lite Wate 3 high early class C cement + 6% Poz mix + 4% gel + 12# salt/sx. mixed @ 12.2#/gal, followed by 375 sxs. class C + 2% calcium chloride mixed @ 14.8#/gal. Plug down @ 8:30 p.m., 10-3-84. Circulated excess of 50 sxs cement. Cementing witnessed by Mr. Pete Hines w/the BLM. W.O.C. 14 $\frac{1}{2}$ hrs. Nippled up & tested csg & BOP stack to 1,000 psi for 30 min. - held. Drilled plug, float & cement. Now drilling ahead w/7-7/8" hole @ 2,396'.

18. I hereby certify that the foregoing is true and correct

SIGNED

M. B. Myers

TITLE

Ass't. to Gen. Supt.

DATE

10-11-84

(This space for Agency Use Only)

APPROVED BY

SWO

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OCT 1 1984

C. L. Shaw

NEW MEXICO

*See Instructions on Reverse Side