

This form is to be filed with the appropriate District Office of the Comptroller not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical resistivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured by this. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Item 36 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1155.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
 T. Salt _____
 B. Salt **776** _____
 T. Yates _____
 T. 7 Rivers _____
 T. Queen **1859** _____
 T. Grayburg **2289** _____
 T. San Andes **2700** _____
 T. Glorieta _____
 T. Paddock _____
 T. Blinckry _____
 T. Tul _____
 T. Pinkard _____
 T. Also _____
 T. Wolfcamp _____
 T. Penn. _____
 T. Cisco (Bough C) _____

T. Canyon _____
 T. Straw _____
 T. Atoka _____
 T. Miss _____
 T. Devonian _____
 T. Silurian _____
 T. Montoya _____
 T. Simpson _____
 T. McKee _____
 T. Eltonburger _____
 T. Gr. Wash _____
 T. Granite _____
 T. Delaware Sand _____
 T. Bone Springs _____
 T. _____
 T. _____

T. Ojo Alano _____
 T. Kirtland Fruitland _____
 T. Pictured Cliffs _____
 T. Cliff House _____
 T. Menefee _____
 T. Mount Lookout _____
 T. Manzano _____
 T. Gallup _____
 T. Bare Greenhorn _____
 T. Dakota _____
 T. Morris _____
 T. Teddito _____
 T. Entrada _____
 T. Wingate _____
 T. Chinle _____
 T. Pennian _____
 T. Penn. "A" _____

Northwestern New Mexico

T. Penn. "B" _____
 T. Penn. "C" _____
 T. Penn. "D" _____
 T. Leadville _____
 T. Madison _____
 T. Elbert _____
 T. McCracken _____
 T. Ignacio Quartzite _____
 T. Granite _____
 T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from to No. 4, from to
 No. 2, from to No. 5, from to
 No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
 No. 2, from to feet.
 No. 3, from to feet.
 No. 4, from to feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
Surf.	345'		Anhydrite				
345'	1435'		Anhydrite				
1435'	1984'		Dolomite				
1984'	2830'		Dolomite, Lime				