CEIVED BY	Artesia, NM 88210	Form Approved. Budget Bureau No. 42–R1424
	LUNUFU SLALES	5. LEASE
M 2 5 198 3 E	EPARTMENT OF THE INTERIOR	NM _34657
111	GLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	IOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
) not use this form ervoir, Use Form 9-	for proposals to drill or to deepen or plug back to a different -331-C for such proposals.)	8. FARM OR LEASE NAME
.oil _{rvn} g	(.as	Amoco Federal
well 🖾 🕠	vell 🖵 other	9. WELL NO.
. NAME OF OP		10. FIELD OR WILDCAT NAME
. ADDRESS OF	OPERATOR	Una N. Hackberry - J. tax - S.F.
	x 4 Loco Hills, NM 88255	11. SEC., T., R., M., OR BLK. AND SURVEY OR
	WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) AT SURFACE:	990 FNL & 1980 FEL	S21, T19S, R31E 12. COUNTY OR PARISH 13. STATE
AT TOP PROD		Eddy NM
AT TOTAL DE		14. API NO.
	OPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR	UDER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3489, GR
. DESCRIBE PR		firectionally drilled, give subsurface locations and
	Spud 12‡" hole @ 11:00 A.M. Ran 8 jts. 8 5/8" 23# casing. Cemu 300 sxs Class "C" 2% CaCl. Circul down @ 8:00 P.M. WOC 18 hrs. T.D. 2425' Ran 2408' of 5½", 17# casing. Cemu	ated 100 sxs to pit. Plug
12-31-84	Ran 8 jts. 8 5/8" 23# casing. Cemu 300 sxs Class "C" 2% CaCl. Circul- down @ 8:00 P.M. WOC 18 hrs. T.D. 2425" Ran 2408' of $5\frac{1}{2}$ ", 17# casing. Cemu setter Lite, 300 sxs Class "C" 2% Circulated 94 sxs to pit.	ated 100 sxs to pit. Plug ented with 300 sxs Pace- CaCl. Plug down @ 4:30 A.M.
12-31-84 ubsurface Safety	Ran 8 jts. 8 5/8" 23# casing. Cemu 300 sxs Class "C" 2% CaCl. Circul- down @ 8:00 P.M. WOC 18 hrs. T.D. 2425' Ran 2408' of $5\frac{1}{2}$ ", 17# casing. Cemu setter Lite, 300 sxs Class "C" 2% Circulated 94 sxs to pit.	ated 100 sxs to pit. Plug ented with 300 sxs Pace- CaCl. Plug down @ 4:30 A.M.
12-31-84 ubsurface Safety 3. I hereby certif	Ran 8 jts. 8 5/8" 23# casing. Cemu 300 sxs Class "C" 2% CaCl. Circula down @ 8:00 P.M. WOC 18 hrs. T.D. 2425" Ran 2408' of 5½", 17# casing. Cemu setter Lite, 300 sxs Class "C" 2% Circulated 94 sxs to pit.	ated 100 sxs to pit. Plug ented with 300 sxs Pace- CaCl. Plug down @ 4:30 A.M. Set @Ft
12-31-84 surface Safety I hereby certif	Ran 8 jts. 8 5/8" 23# casing. Cemu 300 sxs Class "C" 2% CaCl. Circula down @ 8:00 P.M. WOC 18 hrs. T.D. 2425" Ran 2408' of 5½", 17# casing. Cemu setter Lite, 300 sxs Class "C" 2% Circulated 94 sxs to pit.	ated 100 sxs to pit. Plug ented with 300 sxs Pace- CaCl. Plug down @ 4:30 A.M. Set @Ft
12-31-84 ubsurface Safety 8. I hereby certif IGNED IGNED PPROVED BY ONDITIONS OF AP	Ran 8 jts. 8 5/8" 23# casing. Cemu 300 sxs Class "C" 2% CaCl. Circula down @ 8:00 P.M. WOC 18 hrs. T.D. 2425! Ran 2408! of 5½", 17# casing. Cemu setter Lite, 300 sxs Class "C" 2% Circulated 94 sxs to pit. Valve: Manu. and Type fy that the foregoing is true and correct Yuletall TITLE Operator (This space for Federal or State of SPROVAL, IF ANY:	ated 100 sxs to pit. Plug ented with 300 sxs Pace- CaCl. Plug down @ 4:30 A.M.
12-31-84 Ibsurface Safety Ibsurface Safe	Ran 8 jts. 8 5/8" 23# casing. Cemu 300 sxs Class "C" 2% CaCl. Circula down @ 8:00 P.M. WOC 18 hrs. T.D. 2425! Ran 2408! of 5½", 17# casing. Cemu setter Lite, 300 sxs Class "C" 2% Circulated 94 sxs to pit. Valve: Manu. and Type fy that the foregoing is true and correct Multiple (This space for Federal or State of Circulated PA system) TITLE Operator (This space for Federal or State of Circulated PA system)	ated 100 sxs to pit. Plug ented with 300 sxs Pace- CaCl. Plug down @ 4:30 A.M. Set @ Ft