Form 3160-5 (June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-8673

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Well X Gas Well Other PLUGGED AND ABANDONED 8. Well Name and No. 2. Name of Operator Benson Deep FS Fed Com #1 YATES PETROLEUM CORPORATION (505) 748-1471)9. API Well No. 3. Address and Telephone No. 30-015-25121 105 South 4th St., Artesia, NM 88210 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., of Survey Description) Benson Strawn Gas 1830' FNL & 660' FEL of Section 4-T19S-R30E (Unit H. SENE) 11. County or Parish, State Eddy Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION X Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Casing Repair Altering Casing Final Abandonment Notice Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* 6-6-95 - TIH with 2-7/8" tubing to 6050'. Spotted 82 bbls plug mud from 6050-2050' in 5-1/2" casing. Mixed and pumped 30 sacks Class C 2% CaCl2 from 6050-5900' in 5-1/2" casing and 5-1/2" X 7-7/8" annulus. POOH with tubing. WOC. Rigged up wireline. RIH and tagged top of cement at 5840'. Ran and cut 5-1/2" casing at 2700'. Rigged down wireline. Rigged up casing equipment. POOH and laid down 5-1/2" casing. Rigged down casing equipment. RIH with 2-7/8" tubing to 2750'. Mixed and pumped 40 sacks Class C cement from 2750-2650'. POOH with tubing. Shut in overnight. 6-7-95 - TIH with 2-7/8" tubing. Tagged top of cement at 2644'. Spotted 20 bbls plug mud from 2644' to surface. POOH with tubing to 1950'. Mixed and pumped 45 sacks Class C cement from 1950-1850' in 9-5/8" casing. POOH with tubing. WOC 3 hours. TIH with tubing and tagged top of cement at 1839'. POOH with tubing to 400'. Mixed and pumped 40 sacks Class C cement from 400-300' in 9-5/8" casing. POOH with tubing to 50'. Mixed and pumped 20 sacks Class C cement from 50' to surface. POOH and laid down tubing. Cleaned location and installed regulation abandonment marker. PLUGGED AND ABANDONED - FINAL REPORT. Plugging completed 6-6-95. that the foregoing is true and correct June 16, 1995 Production Clerk Title (This space for Federal of State office use) Approved by \_\_\_\_\_\_ Conditions of approval, if any:

or representations as to any matter within its jurisdiction.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements