STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

we, st.Comics acceived	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.5.	
LAND OFFICE	
OPERALOA	

CONDITIONS OF APPROVAL, IF ANY:

OIL CONSERVATION DIVISION

	P. O. BOX 2088	Revised 10-1
SANTA FE	SANTA FE, NEW MEXICO 87501	
U.S.O.S.		Sa. Indicate Type of Lease
LAND OFFICE		State XX Fee _] 5, State Oil & Gas Lease No.
OPERALOR		LG2723
SUNDRY	NOTICES AND REPORTS ON WELLS OSALS TO CRILL ON TO DECEM OR PLUG BACK TO A DIFFERENT RESERVOIR ON FOR PELMIT - " (FORM C-1001) FOR BUCK PROPOSALS.)	
	4 FOR VELMIT = " (FORM C-101) FOR SUCH PROPOSACS.)	7. Unit Agreement Name
Write XX WELL 2. Name of Operator	OTHER-	8. Farm or Lease Name
Metex Pipe & Supply		Southland State
P.O. Box 1037 Artes:	ia, N.M. 88210	9. Well No.
Location of Wall		10. Field and Pool, or Wildaot
UNIT LETTER J . 229	9 FEET FAOM THE SOUTH LINE AND 2290	und. Millman Grayburg
THE EAST LINE, SECTION	7 TOWNSHIP 198 RANGE 28E	NMPM.
	15. Elevation (Show whether DF, RT, GR, etc.) 3519.1 GL	12. County Eddy
16. Check A	ppropriate Box To Indicate Nature of Notice, Repo	ert or Other Data
NOTICE OF INT	TENTION TO: SUBS	EQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OF ALTER CABING	CHANGE PLANS CASING TEST AND CEMENT JO	· [_]
OTHER	OTHER	ιι_
12 Describe Proposed of Completed One	erations (Clearly state all pertinent details, and give pertinent dates	including estimated date of starting any proposi
	rations (areas) state are personal area are a province areas	,, ,, ,, , , , , , , , , ,
work) see RULE 1103.	of 23/01 Log well (CMI/IDT.DLL/MSEL) Logo	rore TD 03/4!
12-23-84 Reach TD	of 2340' Log well (CNL/LDT; DLL/MSFL) Logs	
12-23-84 Reach TD 9:00 pm,	of 2340' Log well (CNL/LDT;DLL/MSFL) Logs verbal permission from Mike Williams of En plug and abandon well. P/A as follows:	
12-23-84 Reach TD 9:00 pm,	verbal permission from Mike Williams of III plug and abandon well. P/A as follows: Set plugs off LaRue Drilling Co. Inc. Rig	≪OCD-Artesia to g #1
12-23-84 Reach TD 9:00 pm,	verbal permission from Mike Williams of IR plug and abandon vell. P/A as follows: Set plugs off LaRue Drilling Co. Inc. Rig 2170'-2270'; 1775'-1875'; 1375'-1475'; 300 and 15 sx. at surface. Released rig 6;00	#1 0'-475' (tagged shoe plug) am, 12-24-84.
12-23-84 Reach TD 9:00 pm,	verbal permission from Mike Williams of Inplug and abandon vell. P/A as follows: Set plugs off LaRue Drilling Co. Inc. Rig 2170'-2270'; 1775'-1875'; 1375'-1475'; 300	#1 0'-475' (tagged shoe plug) am, 12-24-84.
12-23-84 Reach TD 9:00 pm,	verbal permission from Mike Williams of Inplug and abandon vell. P/A as follows: Set plugs off LaRue Drilling Co. Inc. Rig 2170'-2270'; 1775'-1875'; 1375'-1475'; 300 and 15 sx. at surface. Released rig 6;00 dalliburton Class 'C' cement with 2% CaCl	#1 0'-475' (tagged shoe plug) am, 12-24-84.
12-23-84 Reach TD 9:00 pm,	verbal permission from Mike Williams of Inplug and abandon vell. P/A as follows: Set plugs off LaRue Drilling Co. Inc. Rig 2170'-2270'; 1775'-1875'; 1375'-1475'; 300 and 15 sx. at surface. Released rig 6;00 dalliburton Class 'C' cement with 2% CaCl	#1 0'-475' (tagged shoe plug) am, 12-24-84.
12-23-84 Reach TD 9:00 pm,	verbal permission from Mike Williams of Inplug and abandon vell. P/A as follows: Set plugs off LaRue Drilling Co. Inc. Rig 2170'-2270'; 1775'-1875'; 1375'-1475'; 300 and 15 sx. at surface. Released rig 6;00 dalliburton Class 'C' cement with 2% CaCl	#0CD-Artesia to g #1 O'-475' (tagged shoe plug) am, 12-24-84.
12-23-84 Reach TD 9:00 pm,	verbal permission from Mike Williams of Implug and abandon vell. P/A as follows: Set plugs off LaRue Drilling Co. Inc. Rig 2170'-2270'; 1775'-1875'; 1375'-1475'; 300 and 15 sx. at surface. Released rig 6;00 halliburton Class 'C' cement with 2% CaCl 2'; G/B 1877'; QN 1450'; 7-R 713'; Yates 1	#1 0'-475' (tagged shoe plug) am, 12-24-84.
12-23-84 Reach TD 9:00 pm,	verbal permission from Mike Williams of Implug and abandon vell. P/A as follows: Set plugs off LaRue Drilling Co. Inc. Rig 2170'-2270'; 1775'-1875'; 1375'-1475'; 300 and 15 sx. at surface. Released rig 6;00 halliburton Class 'C' cement with 2% CaCl 2'; G/B 1877'; QN 1450'; 7-R 713'; Yates 1	#0CD-Artesia to g #1 O'-475' (tagged shoe plug) am, 12-24-84.
12-23-84 Reach TD 9:00 pm,	verbal permission from Mike Williams of Implug and abandon vell. P/A as follows: Set plugs off LaRue Drilling Co. Inc. Rig 2170'-2270'; 1775'-1875'; 1375'-1475'; 300 and 15 sx. at surface. Released rig 6;00 halliburton Class 'C' cement with 2% CaCl 2'; G/B 1877'; QN 1450'; 7-R 713'; Yates 1	#1 0'-475' (tagged shoe plug) am, 12-24-84.
12-23-84 Reach TD 9:00 pm, LOG TOPS: S/A 222 Will notify NMOCD	verbal permission from Mike Williams of Implug and abandon vell. P/A as follows: Set plugs off LaRue Drilling Co. Inc. Rig 2170'-2270'; 1775'-1875'; 1375'-1475'; 300 and 15 sx. at surface. Released rig 6;00 halliburton Class 'C' cement with 2% CaCl 2'; G/B 1877'; QN 1450'; 7-R 713'; Yates 1	#0CD-Artesia to g #1 O'-475' (tagged shoe plug) am, 12-24-84.
12-23-34 Reach TD 9:00 pm, LOG TOPS: S/A 222 Will notify NMOCD	verbal permission from Mike Williams of Implug and abandon vell. P/A as follows: Set plugs off LaRue Drilling Co. Inc. Rig 2170'-2270'; 1775'-1875'; 1375'-1475'; 300 and 15 sx. at surface. Released rig 6;00 Malliburton Class 'C' cement with 2% CaCl 2'; G/B 1877'; QN 1450'; 7-R 713'; Yates the when ready for final inspection.	#1 0'-475' (tagged shoe plug) am, 12-24-84.