Artesia, NM 8821	Form Approved. Budget Bureau No. 42–R1424
UNITED STATES	5. LEASE
EPARTMENT OF THE INTERIOR	LC-029392-B
GECLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OTICES AND REPORTS ON WELLS	
-331-C for such proposals.)	8. FARM OR LEASE NAME Scottsdale
well other	9. WELL NO.
	10. FIFLD OR WILDCAT NAME
	Shugart-Queen Value-SR-D-G
	11. SEC., T., R., M., OR BLK. AND SURVEY OR
WELL (REPORT LOCATION CLEARLY. See space 1	
330 FNL 990 FEL	12. COUNTY OR PARISH 13. STATE
D. INTERVAL: Same	Eddy New Mexico
PTH: Same	14. API NO.
OPRIATE BOX TO INDICATE NATURE OF NOTIC OTHER DATA	E, 15. ELEVATIONS (\$HOW DF, KDB, AND WD)
	3658GR
ction Casing & Logging ROPOSED OR COMPLETED OPERATIONS (Clearly	state all pertinent details, and give pertinent dates,
1 true vertical depths for all markers and zones pert	is directionally drilled, give subsurface locations and tinent to this work.)*
d true vertical depths for all markers and zones pert	is directionally drilled, give subsurface locations and inent to this work.)*
d true vertical depths for all markers and zones pert T.D. 4503' - at 9:30 AM	is directionally drilled, give subsurrace locations and inent to this work.)*
d true vertical depths for all markers and zones pert T.D. 4503' - at 9:30 AM T.D. 4503' - Ran Schlumberger CN (4529.04') of 4 1/2", 10.5# S.T. with 1500 sxs. DLW IV, 5# salt p	IL-LDT-GR-Calip, DDL-MSFL - ran 108 joi &.C. casing set at 4502' K.B cement per sx., 1/4# D29 Celo Flake - tailed
d true vertical depths for all markers and zones pert T.D. 4503' - at 9:30 AM T.D. 4503' - Ran Schlumberger CN (4529.04') of 4 1/2", 10.5# S.T. with 1500 sxs. DLW IV, 5# salt per 600 sxs. DLW IV with 5# salt per	IL-LDT-GR-Calip, DDL-MSFL - ran 108 joi &.C. casing set at 4502' K.B cement per sx., 1/4# D29 Celo Flake - tailed
d true vertical depths for all markers and zones pert T.D. 4503' - at 9:30 AM T.D. 4503' - Ran Schlumberger CN (4529.04') of 4 1/2", 10.5# S.T. with 1500 sxs. DLW IV, 5# salt per 600 sxs. DLW IV with 5# salt per plug down at 4:30 PM	IL-LDT-GR-Calip, DDL-MSFL - ran 108 joi &.C. casing set at 4502' K.B cement per sx., 1/4# D29 Celo Flake - tailed
d true vertical depths for all markers and zones pert T.D. 4503' - at 9:30 AM T.D. 4503' - Ran Schlumberger CN (4529.04') of 4 1/2", 10.5# S.T. with 1500 sxs. DLW IV, 5# salt p 600 sxs. DLW IV with 5# salt per plug down at 4:30 PM T.D. 4503' - W.A.C.	IL-LDT-GR-Calip, DDL-MSFL - ran 108 joi &.C. casing set at 4502' K.B cement ber sx., 1/4# D29 Celo Flake - tailed r sx circulated 75 sxs. to surface -
d true vertical depths for all markers and zones pert T.D. 4503' - at 9:30 AM T.D. 4503' - Ran Schlumberger CN (4529.04') of 4 1/2", 10.5# S.T. with 1500 sxs. DLW IV, 5# salt p 600 sxs. DLW IV with 5# salt per plug down at 4:30 PM T.D. 4503' - W.A.C. y Valve: Manu. and Type	HL-LDT-GR-Calip, DDL-MSFL - ran 108 joi &.C. casing set at 4502' K.B cement per sx., 1/4# D29 Celo Flake - tailed r sx circulated 75 sxs. to surface -
<pre>d true vertical depths for all markers and zones pert T.D. 4503' - at 9:30 AM T.D. 4503' - Ran Schlumberger CN (4529.04') of 4 1/2", 10.5# S.T. with 1500 sxs. DLW IV, 5# salt p 600 sxs. DLW IV with 5# salt per plug down at 4:30 PM T.D. 4503' - W.A.C. y Valve: Manu. and Type ity that the foregoing is true and conject</pre>	HL-LDT-GR-Calip, DDL-MSFL - ran 108 joi &.C. casing set at 4502' K.B cement per sx., 1/4# D29 Celo Flake - tailed r sx circulated 75 sxs. to surface -
d true vertical depths for all markers and zones pert T.D. 4503' - at 9:30 AM T.D. 4503' - Ran Schlumberger CN (4529.04') of 4 1/2", 10.5# S.T. with 1500 sxs. DLW IV, 5# salt p 600 sxs. DLW IV with 5# salt per plug down at 4:30 PM T.D. 4503' - W.A.C. y Valve: Manu. and Type ity that the foregoing is true and conject Marke Presider	IL-LDT-GR-Calip, DDL-MSFL - ran 108 joi &.C. casing set at 4502' K.B cement ber sx., 1/4# D29 Celo Flake - tailed r sx circulated 75 sxs. to surface - Set @Ft.
d true vertical depths for all markers and zones pert T.D. 4503' - at 9:30 AM T.D. 4503' - Ran Schlumberger CN (4529.04') of 4 1/2", 10.5# S.T. with 1500 sxs. DLW IV, 5# salt p 600 sxs. DLW IV with 5# salt per plug down at 4:30 PM T.D. 4503' - W.A.C. y Valve: Manu. and Type ity that the foregoine is true and conject Presider (The space for Federal or Sta	IL-LDT-GR-Calip, DDL-MSFL - ran 108 joi &.C. casing set at 4502' K.B cement ber sx., 1/4# D29 Celo Flake - tailed r sx circulated 75 sxs. to surface - Set @Ft. ntFt. ntFt. ate office use)
d true vertical depths for all markers and zones pert T.D. 4503' - at 9:30 AM T.D. 4503' - Ran Schlumberger CN (4529.04') of 4 1/2", 10.5# S.T. with 1500 sxs. DLW IV, 5# salt p 600 sxs. DLW IV with 5# salt per plug down at 4:30 PM T.D. 4503' - W.A.C. y Valve: Manu. and Type ity that the foregoine is true and conject Presider (The space for Federal or Sta	IL-LDT-GR-Calip, DDL-MSFL - ran 108 joi &.C. casing set at 4502' K.B cement ber sx., 1/4# D29 Celo Flake - tailed r sx circulated 75 sxs. to surface - Set @ft.
d true vertical depths for all markers and zones pert T.D. 4503' - at 9:30 AM T.D. 4503' - Ran Schlumberger CN (4529.04') of 4 1/2", 10.5# S.T. with 1500 sxs. DLW IV, 5# salt p 600 sxs. DLW IV with 5# salt per plug down at 4:30 PM T.D. 4503' - W.O.C. y Valve: Manu. and Type ity that the foregoing is true and conject Presider (This space for Federal or Sta	<pre>HL-LDT-GR-Calip, DDL-MSFL - ran 108 joi &.C. casing set at 4502' K.B cement ber sx., 1/4# D29 Celo Flake - tailed r sx circulated 75 sxs. to surface - </pre>
	EPARTMENT OF THE INTERIOR GECLOGICAL SURVEY OTICES AND REPORTS ON WELLS for proposals to drill or to deepen or plug back to a differ -331-C for such proposals.) EASE Well other ERATOR and Gas Corporation OPERATOR CE BOX 2523, Roswell, NM 88201 E WELL (REPORT LOCATION CLEARLY. See space 330 FNL 990 FEL D. INTERVAL: Same PTH: Same OPRIATE BOX TO INDICATE NATURE OF NOTIC OTHER DATA PROVAL TO: SUBSEQUENT REPORT OF: JT-OFF CE CASING CE CASING CE Casing & Logging

dsf

•

$\hat{\mathbf{A}}$	
Carlibad.	
alutat.	NEW MEXICO

*See Instructions on Reverse Side