

UNITED STATES Artesia, NM 88210

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other

2. NAME OF OPERATOR  
Siete Oil and Gas Corporation ✓

3. ADDRESS OF OPERATOR  
P.O. Box 2523, Roswell, New Mexico 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1830' FNL, 660' FWL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☒  
☒  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED BY

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

APR 23 1985

O. C. D.

ARTESIA, OFFICE

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 3/27/85 - T.D. 5256' - Schlumberger Perforated as follows: 4295, 4296.5, 4298, 4299.5, 4301, 4302.5, 4304, 4305.5, 4307, 4308.5, 4310, 4311.5, 4313, 4314.5 & 4316 - 15 Shots - Dowell Schlumberger acidized with 1500 gals. HCL acid - balled out ISIP 1500 PSI - well flowed for 30 minutes - swab 6 runs - no show.
- 3/28/85 - T.D. 5256' - Dowell fraced zone 4295' to 4316' with 17,000 gals. crosslink & 23,000 lbs. 12/20 sand - ISIP 1800 PSI - shut well in 4 hrs. - Tbg. pressure 1150 PSI - open well to flow for 2 1/2 hrs. - swab rest of day - slight show of oil.
- 3/29/85 - T.D. 5256' - swab test - 5% oil cut.
- 3/30/85 - T.D. 5256' - swab test - 5% oil cut.
- 3/31/85 - T.D. 5256' - swab test - 10% oil cut - hang well on pump.
- 4/01/85 - T.D. 5256' - pumping & testing.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Consultant DATE April 18, 1985

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

APR 21 1985