

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Exxon Corp			Lease New Mexico ES State Com		Well # 1
Location of Well	Unit 0	Section 7	Township 19	Range 24	County Eddy
Drilling Contractor	—		Type of Equipment Rotary		

* **Witness**

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	54.5		300	160 SX-Circ
* 12 1/4	8 5/8	24.0		1700	500 SX-Circ
7 7/8	5 1/2	14-15.5-17		8800	620 SX-4100

Casing Data:

Surface 45 joints of 8 7/8 inch 24 # Grade J-55

yes (Approved) (Rejected)

Inspected by BW Weaver date 6-26-85

Cementing Program

Size of hole 12 1/4 Size of Casing 8 7/8 Sacks cement required 250

Type of Shoe used Guide Float collar used Float Btm 3 jts welded yes

TD of hole 1725 Set 1721 Feet of 8 7/8 Inch 24 # Grade J-55

New-used csg. @ 1721 with 250 sacks neat cement around shoe

+ 750 sax Hawco lite additives 1/4 Flo Seal #5 Gilsonite

Plug down @ 2:00 (~~AM~~) (PM) Date 6-27-85

Cement circulated yes No. of Sacks 230

Cemented by Hawco Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: