

c/sf

JUL 30 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
O.C.D. Use "APPLICATION FOR PERMIT—" for such proposals.)

ARTESIA, OFFICE
OIL WELL ☐ GAS WELL ☐ OTHER ☒

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980 FNL & 660 FWL, Sec. 35-T20S-R21E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4460' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 25336

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Deer Canyon South ACK Federal
Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit E, Sec. 35-T20S-R21E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☒

(Other) Perforate, Treat ☒

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 7-8-85. Set CIBP at 7800' w/35' cement on top. WIH and perforated 7349-57' w/16 .34" holes (2 SPF).
7-9-85. Acidized perfs 7349-57' (16 holes) w/1000 gals 7½% MCA acid, N₂ and 18 ball sealers.
7-10-85. WIH and perforated 7266-70' w/10 .34" holes. Acidized perfs 7266-70' w/1000 gals 15% NEFE acid, N₂ and 8 ball sealers.
7-13-85. WIH and perforated 7173-78' w/10 .34" holes.
7-15-85. Acidized perfs 7173-78' (10 holes) w/1000 gals 15% NEFE acid, 2% KCL and 8 ball sealers.
7-16-85. WIH and perforated 5977-87' w/20 .34" holes (2 SPF).
7-17-85. Acidized perfs 5977-87' (20 holes) w/1500 gals 15% NEFE acid, N₂ and ball sealers.
7-23-85. Re-acidized perfs 5977-87' (20 holes) w/10000 gals 15% NEFE Retarded acid + CO₂.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Supervisor

DATE 7-24-85

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUL 25 1985

*See Instructions on Reverse Side