

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS ON RECEIVED

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.
LC-063622

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Tenneco Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

N. Hackberry Yates 7-Rivers

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

S.21, T19S, R31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

SEP 01 '88

2. NAME OF OPERATOR

Cantro Exploration, Inc.

3. ADDRESS OF OPERATOR PO Box 700150, San Antonio, TX 78270

O. C. D.
ARTESIA, OFFICE

AGENT: PO Box 196, Artesia, NM 88211

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

2240' FSL & 1650' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3495' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

Plug & Abandon x

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Propose to pump the following plugs to abandon the above captioned well. All plugs inside 5½" casing except bottom plug which has 33' of 4" open hole. The cement on the 5½" casing was circulated to the surface when run.

Procedure I - pump 20 sx Class C Cement from 2310' to 2129'. Allow to set & tag.

II - pump 5 sx Class C Cement from 2025' to 1975'. Base Salt.

III - pump 5 sx. Class C Cement from 708' to 658'. Top Salt.

IV - pump 10 sx. Class C Cement from 350' to 250'. Surface Casing Shoe.

V - pump 5 sx. Class C Cement at surface.

Dry hole marker will be installed and surface location will be restored and seeded. BLM will be notified in advance to all work.

RECEIVED
AUG 10 10 40 AM '88
CANTO
AREA

18. I certify that the foregoing is true and correct

SIGNED Martin Muncy for Robert Green

TO BE Agent

DATE 8/8/88

(This space is for use of State office use)

APPROVED BY ORIG. SGD. RAJ GIRI
CONDITIONS OF CHIEF MINERAL RESOURCES

TITLE

DATE 8-31-88

*See Instructions on Reverse Side