

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-663622

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different depth.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Cantro Exploration, Inc.

3. ADDRESS OF OPERATOR

PO Box 700150, San Antonio, TX 78270

SEP 01 '88
D. D.
ARTESIA OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

790' FSL & 2310' IEL

8. FARM OR LEASE NAME

Tenneco Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

N. Hackberry Yates 7-Rivers

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 21, T19S, R31E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3529' GL

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

Plug & Abandon

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to pump the following plugs to abandon the above captioned well. All plugs inside 5 1/2" casing. The cement on the 5 1/2" casing was circulated to surface when run.

Procedure I - pump 15 sx Class C cement from 2291' to 2048'. Allow to set and tag.

II - pump 5 sx Class C cement from 2048' to 1998'. Base Salt.

III - pump 5 sx Class C cement from 759' to 709'. Top Salt.

IV - pump 10 sx Class C cement from 350' to 250'. Surface Casing Shoe.

V - pump 5 sx Class C cement from 50' to surface.

Dry hole marker will be installed and location will be restored and seeded. BLM will be notified prior to all work.

18. I hereby certify that the foregoing is true and correct

SIGNATURE

Martin Murry

TITLE

Agent

DATE

8/8/88

(This space for Federal or State office use)

for Robert Green

APPROVED BY

CHIEF, MINERAL RESOURCES

TITLE

DATE

8/31/88

CONDITIONS OF APPROVAL, IF ANY

*See Instructions on Reverse Side