STATE OF NEW MEXICO	
ENERGY AND MINERALS DEPARTMENT OIL CONSERVA TORRECTION OF CONSERVA DISTRIBUTION P. O. BOX 2088 SANTA FE, NEW 1EXIGNO 1985 U.S.O.S. LAND OFFICE OPERATOR OIL CONSERVA FOR BOX 2088 1EXIGNO 1985 O. C. D. ARTESIA, OFFICE	Form C-103 Revised 19-1-78 Sa. Indicate Type of Lesse State X Fee 5. State Oil & Gas Lesse No. LG 6459
SUNDRY NOTICES AND REPORTS ON WELLS 100 NOT USE THIS FORM FOR PROPOSALS TO CRILL OR TO DEEPEN OR PLUG SACE TO A DIFFERENT RESERVOIM. 100 NOT USE TARPLICATION FOR PERMIT - FORM C-1011 FOR SUCH PROPOSALS.	
I. OIL GAB X OTHER-	7. Unit Agreement Name
Yates Petroleum Corporation	8. Form or Lease Name Agave AAJ State
207 South 4th St., Artesia, NM 88210	9. Well No. 2
4. Location of Well WHIT LETTER K 1980 FEET FROM THE SOUTH LINE AND 1980 FEET FROM	Undesignated Morrow
West LINE, SECTION 32 TOWNSHIP 195 RANGE 24E HMPM.	
15. Elevation (Show whether DF, RT, GR, etc.) 3826 GR	12. County Eddy
Check Appropriate Box To Indicate Nature of Notice, Report or Oth NOTICE OF INTENTION TO: SUBSEQUENT	er Data REPORT OF:
PERFORM REMEDIAL WORK TEMPORAPILY ABAHDON PULL OR ALTER CASING CHANGE PLANS CHANGE PLANS OTHER OTHER	PLUG AND ADARDONMENT
отнея	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.	estimated date of starting any proposed
Spudded 17-1/2" hole at 5:30 PM 8-7-85. Lost returns at 87, regained. Dry drilled. Ran 13 jts 13-3/8" 54.5# J-55 casing set 376'. Guide she float set 337'. Cemented w/150 sx Halliburton Lite Thixset + 10#/sx (Flocele and .3% CaCl2. Tailed in w/400 sx Cl "C" + 2% CaCl2. Comp. 1250 psi in 12 hrs. PD 10:00 PM 8-8-85. Bumped plug to 1000 psi, relokay. Cement did not circulate. WOC 6 hrs. Ran 1". Tagged cement Cl "C" w/3% CaCl2. PD 4:45 AM 8-9-85. WOC 2 hrs. Ran 1". Tagged ce 50 sx Cl "C" w/3% CaCl2. PD 6:48 AM 8-9-85. WOC 2 hrs. Ran 1". Tag 50 sx Cl "C" w/3% CaCl2. PD 9:20 AM 8-9-85. WOC 2 hrs. Ran 1". Tag 150 sx Cl "C" Neat. PD 11:30 AM 8-9-85. Circulated 5 sx. WOC. Dril WOC 17 hrs. Cut off and welded on flow nipple. Reduced hole to 11". resumed drilling.	noe set 376'. Insert Gilsonite + 1/2#/sx strength of cement - leased pressure, held 251'. Spotted 50 sx ement 202'. Spotted gged cement 184'. Spotted gged cement 90'. Spotted lled out 3:00 PM 8-9-85.
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	

DATE 8-14-85 Original Signed By AUG 21 1985 Las A. Clements Supervisor District II