

~~CONFIDENTIAL~~

C/SF

Form 9-331
Dec 1973

NM OIL CONS. COMMISSION

Drawer DD
Artesia, NM 88210

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
Siete Oil and Gas Corporation

3. ADDRESS OF OPERATOR
P.O. Box 2523, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2310' FNL, 1980' FWL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

RECEIVED BY
JAN 8 0 1987
O. C. D.
ARTESIA, OFFICE

5. LEASE
LC065680

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Blackhawk Federal

9. WELL NO.
2

10. FIELD OR WILDCAT NAME
Shugart

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 24: T-18-S, R-31-E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.
30-015-25360

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3702' GR

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input checked="" type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)			

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/21/85 - Schlumberger perforated zone 4263' to 4272 - 7 perms - Dowell Schlumberger acidized with 1000 gals. 15% HCL Acid - fraced with 16,000 gals. crosslink + 27,000# 12/20 sand - non productive

8/24/85 - set cast iron bridge plug @4204'

8/26/85 - Schlumberger perforated zone 3750' to 3791' - 11 perms - acidized with 1000 gals. 15% hcl acid + ball sealers - fraced with 15,000 gals. crosslink 15,000# 12/20 sand

9/12/85 - refrac 3750' to 3791 with 29,000 gals. crosslink, 4000# 100 mesh sand, 20,500# 20/40, 21,000# 12/20 sand.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. Justice TITLE Consultant DATE September 19, 1985

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

OCT 8 1985