

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

c/sf

5. LEASE DESIGNATION AND SERIAL NO.

LC-029388 (d)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Johnson "B" Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Undesignated (Bone Springs)  
TAMANO

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 11, T18S, R31E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1. OIL ☒ GAS ☐ OTHER ☐  
WELL WELL
2. NAME OF OPERATOR  
Marathon Oil Company ✓
3. ADDRESS OF OPERATOR  
P. O. Box 2409 Hobbs, NM 88240
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface  
660' FNL & 1980' FWL
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
Not Available GL 3735', KB 3764.20'
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANE

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Completion

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Swabbed on well from 01-02-86 to 01-16-86. Released the RTTS packer and retrieved the RBP. Went in the hole with a mud joint, perforated sub, seating nipple, 10 joints of 2 3/8" tubing and Baker anchor catcher on 2 3/8" tubing. Set the seating nipple at 8635' and set the anchor with 16,000 pounds of tension. Nippled up the wellhead. Went in the hole with a 2" x 1 1/4" x 16' pump on 238 - 3/4" and 105 - 7/8" steel rods. Set an Oilwell C-320-256-120 pumping unit. Hooked up an Ajax engine and started the well pumping to a frac tank on 01-30-86.

ACCEPTED FOR RECORD

*Swd*  
FEB 6 1986

CAPISBARD, NEW MEXICO

RECEIVED BY

FEB 07 1986

O. C. D.

ARTESIA OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

*Steven A. Pohler*  
Steven A. Pohler

TITLE Production Engineer

DATE 02-03-86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side