Form 3160-5 (November 1983) (Formerly 9-331) DEPARTMLIAT OF THE INTERBUREAU OF LAND MANAGEMENT	_	Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO LC-063622
SUNDRY NOTICES AND REPORTS (Do not use this form for proposals to drill or to deepen or plug Use "APPLICATION FOR PERMIT—" for such	ON WELLSED s back to a different reservoir. proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS WELL OTHER	Nov 15 8 53 AM '93	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	CAL. HOE	8. FARM OR LEASE NAME
CANTRO EXPLORATION, INC.	AREA LIEKS	TENNECO FEDERAL
3. ADDRESS OF OPERATOR PO BOX 700150, SAN ANTONI AGENT: PO BOX 196 ARTESIA, NM 88210	O, TX 78270 RECEIVED	9. WELL NO.
 LOCATION OF WELL (Report location clearly and in accordance with at See also space 17 below.) At surface 	DEC 0 8 1993	N. HACKBERRY YATES 7 RIVERS
1650' FNL & 790' FEL	Ç. I. D.	11. SBC., T., R., M., OR BLK. AND SURVEY OF AREA SEC. 29, T19S, R31E
14. PERMIT NO. 15. ELEVATIONS (Show whether	DF, RT, CR, etc.)	12. COUNTY OR PARISH 13. STATE
3476' G	L	EDDY NM
16. Check Appropriate Box To Indicate	Nature of Notice, Report, or C	Other Data
NOTICE OF INTENTION TO:	\$UBSEQ!	TENT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACT BE TREAT MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE ABANDON®	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL CHANGE PLANS (Other)	(Other)(Note: Report results	of multiple completion on Well etion Report and Log form.)
17. DESCRIEE PROPOSED OR COMPLETED OFFRATIONS (Clearly state all perting proposed work. If well is directionally drilled, give subsurface location to this work.)* PERFORMED THE FOLLOWING TO PLUG AND ABA 1. RIG UP PULLING UNIT 2. TOH WITH PUMP— LAY DOWN 90 3/4" ROD 3. TOH WITH 2 3/8" TUBING. 69 JTS.=22 4. TIH WITH 2 3/8" TUBING TO 2157'. SE (LOADED HOLE W/ GEL H_0) 5. TAG CEMENT PLUG AS 2025'. 6. TOH LAYING DOWN 2 3/8" TUBING AND S 2 HRS. AND TAG. 7. TAG CEMENT PLUG AT 235'. 8. TOH LAYING DOWN 2 3/8" TUBING AND S 9. TOH LAYING DOWN 2 3/8" TUBING. TOF 10. BREAK OFF WELL HEAD — NOT ABLE TO 11. RIG DOWN PULLING UNIT. DRY HOLE MARKER HAS BEEN INSTALLED AND AND RESEEDED.	NDON THE ABOVE CAPTION S & PUMP & GAS ANCHOR. 667.05 + MUD ANCHOR NOT CT CEMENT PLUG 2157' - SET AT 356'. SET CEMENT OFF CEMENT TO SURFACE BREAK OUT 5½" CASING S	ed depths for all markers and gones perti- ED WELL ON 10-29-93. 1-6' & 3-4' PONY RODS. TALLIED. 2090'. WAIT 2 HRS. AND TAG. T PLUG AT 356'-250'. WAIT PLUG AT 58'-SURFACE. WAGE. 1-7-94 PLUG AT 58'-SURFACE.
AS OF 11-8-93 LOCATION HAS BEEN RESTOR PLUG & ABANDON OPERATION HAS BEEN COMPL 18. I hereby certify that the foregoing is true and correct		BEEN PUT ACROSS ROAD. DATE 11-11-93
	- Binos/Routi	
(This space for Federal or State office use)	D.	EC. 67 1983
APPROVED BY (GRIG. SGD.) DAVID R. GLASSIE CONDITIONS OF APPROVAL, IF ANY:	Petroleum Engineer	DATE DEC 9 7 1983

*See Instructions on Reverse Side

Approved as to plugging of the well bore.
Lability under bond is retained until
surface restoration is completed.