

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR

Robert N. Enfield

3. ADDRESS OF OPERATOR

P.O. Box 2431, Santa Fe, NM 87504

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL & 1980' FWL of Sec. 12

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☒

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Total depth of 8018' was reached on 3/22/86. Logs were run & well was considered dry.

Plugs will be set as follows (all plugs Class "H" cement):

50 sx plug from 7807' - 7957'

50 sx plug from 6840' - 6990'

50 sx plug from 5164' - 5314'

35 sx plug from 3214' - 3314'

50 sx plug from 2440' - 2360'

Tag top of cement

35 sx plug from 377' - 277'

2 sx plug from 50' - surface

Dry hole marker to be installed

Pits to be fenced waiting for them to dry.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Robert N. Enfield*

TITLE

Operator

DATE

4/22/86

Robert N. Enfield

(This space for Federal or State office use)

APPROVED BY

*Charles S. D...*

TITLE

DATE

4-22-86

CONDITIONS OF APPROVAL, IF ANY: