

UNITED STATES OF AMERICA
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-14206

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

B&B Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat San Andres

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 12-T19S-R26E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

RALPH NIX OIL, INC.

3. ADDRESS OF OPERATOR

P. O. Box 440, Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL and 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3307.5' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) Spud, set csg. ☒

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/16/86 7:00 am spudded w/reverse unit. Drill out plugs and clean hole to 2803' GL.

12/19/86 Ran down to 2803' GL. TD 2803' GL. Pumped 50 sx plug Class C cmt w/2% CACL per sx. Wt. 14.8 ppg.

12/20/86 Tag top of plug 2667' GL. Dressed plug 2680' GL, TD.

12/23/86 RIH w/64 jts. 5 1/2" 15.5# J-55 8rd LT&C csg, set at 2677.46' GL. Cmt. w/250 sx Class C w/2% CACL per sx. Plug down 4:51 pm.

12/24/86 Run temp. survey. Top of cmt. at 1220' FS.

12/26/86 Log w/CCL/GR tools. TD at 2632' KB. Tested csg. 1530 psi for 30 min. Test OK.

ACCEPTED FOR RECORD

JAN 07 1987

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE President

DATE 12/31/86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: