

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR  
Robert N. Enfield

3. ADDRESS OF OPERATOR  
P.O. Box 2431, Santa Fe, NM 87504-2431

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1835' FNL & 2310' FWL of Sec. 5  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) INTERMEDIATE CASING ☒

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM-45227

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Chevron Federal Comm.

9. WELL NO.

10. FIELD OR WILDCAT NAME  
Undesignated Penn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 5, T19S, R27E

12. COUNTY OR PARISH  
Eddy

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3280 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled a 12-1/4" hole from 305' to 1243"; 11" hole from 1243' to 2450'. TD intermediate hole at 1:30 PM March 29, 1986. Ran 8-5/8", 24#/ft., J-55, ST&C casing set at 2458" (note casing measurement indicated a total depth of 2458' K.B.). Cemented w/900 sacks of Halliburton Lite with 1/4#/sk. flocele & 5#/sk. Gilsonite (12.5#/gal, 1.91 cu. ft.) tailed in w/300 sx Class "C" cement w/2% CACLs (14.8#/gal, 1.32 cu. ft.). Displaced w/154.3 barrels F.W. Circulated 235 sx to pit. Bumped plug w/1500 PSIG at 10:20 PM, March 29, 1986, float held OK. Tested blind rams to 1600 PSIG for 45 minutes, tested OK. Tested pipe rams to 1600 PSIG for 45 minutes, tested OK.

ACCEPTED FOR RECORD

266

MAY 21 1986

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert N. Enfield

TITLE Operator

DATE 5/19/86

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_