

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR  
Robert N. Enfield

3. ADDRESS OF OPERATOR  
P.O. Box 2431, Santa Fe, NM 87504-2431

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1835' FNL & 2310' FWL of Sec. 5  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) Log + PRODUCTION CASING X

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

April 17, 1986 Total depth 7922'. Ran logs. Ran 4-1/2", 11.60#/ft., K-55 LT&C casing set at 7922'. Cemented w/425 sx Halliburton Class "H" with 3/10 of 1% CFR-2 and 5#/sk KCL (mixed 15.6#/gal., 1.18 cu. ft./sk). Displaced plug w/125 barrels fresh water at 6 BPM. Did not bump plug, pumped calculated displacement plus 1 barrel. Released pressure, float held

ACCEPTED FOR RECORD

MAY 21 1986

CARLSBAD, NEW MEXICO

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED Robert N. Enfield TITLE Operator DATE 5/19/86  
(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: