

WRS COMPLETION REPORT

COMPLETIONS SEC 13 TWP 18S RGE 31E
PI# 30-1-0004 10/20/86 30-015-25594-0000 PAGE 1

NMEX EDDY * 330FSL 990FEL SEC SE SE
STATE COUNTY FOOTAGE SPOT
YATES HARVEY E WD DO
OPERATOR WELL CLASS INIT FIN
1 SOUTH TAYLOR "13" FEDERAL
WELL NO. LEASE NAME
3728KB 3716GR EDDY CO UNDESIG
OPER ELEV FIELD POOL AREA
API 30-015-25594-0000

LEASE TYPE NO. PERMIT OR WELL I.D. NO.
07/24/1986 09/25/1986 ROTARY OIL
SPUD DATE COMP. DATE TYPE TOOL STATUS
5350 DELAWARE PETERSON DRLG 3 RIG SUB 11
PROJ. DEPTH PROJ. FORM CONTRACTOR
DTD 5410 PB 5083 FM/TD DELAWARE
DRILLERS T.D. LOG T.D. PLUG BACK TD OLD T.D. FORM T.D.

LOCATION DESCRIPTION

10 MI SE LOCO HILLS, NM

WELL IDENTIFICATION/CHANGES

SEC CHGD FROM 18
FIELD CHGD FROM WILDCAT

CASING/LINER DATA

CSG 8 5/8 @ 353 W/ 250 SACKS 01
CSG 5 1/2 @ 5410 W/ 2025 SACKS 02
PERF & CSG SQZD W/600 SX @ 5119 W/4 SHOTS
CMT RET @ 5100
DOC & BRPG TO 5400

TUBING DATA

TBG 2 3/8 AT 4970

INITIAL POTENTIAL

IPP 98BOPD 105 MCFD 120BW 24HRS
DELAWARE PERF JET W/ 2/IT 5063- 5063 006
PERF 5063- 5063
ACID 5063- 5063 500GALS
15%
SGFR 5063- 5063 20000GALS 38000LBS SAND
8000 LBS 100 MESH ADDTVGEL

CONTINUED IC# 300157005386

Copyrighted
Reproduction
Prohibited



Petroleum Information
CORPORATION

PI-WRS-GET
Form No 187

COMPLETIONS SEC 13 TWP 18S RGE 31E
PI# 30-T-0004 10/20/86 30-015-25594-0000 PAGE 2

YATES HARVEY E WD DO
1 SOUTH TAYLOR "13" FEDERAL

INITIAL POTENTIAL

30000 LBS 20/40
GTY 32.0 GOR 1071

TYPE	FORMATION	LTH	TOP DEPTH/SUB	BSE DEPTH/SUB
LOG	RUSTLER		869 2859	
LOG	YATES		2444 1284	
LOG	SVN RVRS		2802 926	
LOG	BOWERS		3282 446	
LOG	QUEEN		3518 210	
LOG	PENROSE		3764 -36	
LOG	GRAYBURG		4098 -370	
LOG	PREMIER		4474 -746	
LOG	SN ANDRS		4548 -820	
LOG	DELAWARE		4714 -986	

PRODUCTION TEST DATA

PTS 1UO
DELAWARE PERF 5059- 5068 003
PERF 5059- 5068
ACID 5059- 5068 2000GALS
SGFR 5059- 5068 20000GALS 28000LBS SAND

SQZD 5059- 5068 ADDTVGEL
SWBD 168 BF (5% OIL) W/ 100S
CMT RET @ 5000
SQZD & DOC TO 5400

DELAWARE PERF 5182- 5210 GROSS 004
PERF 5182- 5186 5200- 5210
ACID 5182- 5210 3600GALS
15%

PTS 1UO
DELAWARE PERF 5182- 5210 GROSS 005
PERF 5182- 5210
SGFR 5182- 5210 20000GALS 28000LBS SAND
BRPG 5182- 5210 DEPTH 5083 ADDTVGEL
SWBD 96 BF (20% OIL)

CONTINUED