

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

(See other instructions on reverse side)

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. REVR. ☐ Other ☐

2. NAME OF OPERATOR

Siete Oil & Gas Corporation ✓

3. ADDRESS OF OPERATOR

P. O. Box 2523, Roswell, NM 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 790'FNL & 940'FEL

At top prod. interval reported below Same

At total depth Same

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

4/10/86

16. DATE T.D. REACHED

4/20/86

17. DATE COMPL. (Ready to prod.)

4/27/86

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

3705'GR

19. ELEV. CASINGHEAD

3707'GR

20. TOTAL DEPTH, MD & TVD

4450'

21. PLUG, BACK T.D., MD & TVD

4407'

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

4450'

CABLE TOOLS

24. PRODUCING INTERVAL(S). OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

4301' to 4306' - Grayburg

25. WAS DIRECTIONAL SURVEY MADE

Yes

26. TYPE ELECTRIC AND OTHER LOGS RUN

Schlumberger CNL & Bond Log

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	358'	12 1/4"	230 sxs "C" 2% CaCl ²	N/A
5 1/2"	17#	4449'	7 7/8"	700 sxs High Early III - 10# salt - 200 sxs 50/50 Poz - 6# salt	N/A

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)
N/A				

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 3/8"	4285'	N/A

31. PERFORATION RECORD (Interval, size and number)

4301' - 4306' - .38 - 11 shots

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4301' - 4306'	500 gal. 15% acid, 20,000 gal. 30# Crosslink, 2,000# 100 mesh 20,000# 20/40, 20,000# 12/20

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
		Pumping (American 160)				Producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
4/26/86	24	N/A	108	108	70	78	648/1
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
N/A	N/A	108	108	70	78		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Vented

TEST WITNESSED BY

Jim Ikard

35. LIST OF ATTACHMENTS

Schlumberger CNL - Bond Log - GARRISON, NM-124, SVC-D16, C-104

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED


[Signature]

TITLE Production Supervisor

DATE 4/29/86

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, flowing and shut-in pressures, and recoveries);					38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.		NAME	TOP	TRUE VERT. DEPTH
Base Salt	2186'						
Yates	2352'						
Seven Rivers	2534'						
Bowers	3278'						
Queen	3508'						
Grayburg	4048'						
San Andres	4415'						




LaRue Drilling Co., Inc. — Oil Well Drilling Contractors

P. O. BOX 2523
470

ARTESIA, NEW MEXICO 88210

April 30, 1986

Siete Oil and Gas
PO Box 2523
Roswell, NM 88201



Re: Geronimo Federal #6
790' FNL & 940' FEL
Sec. 24, T18S, R31E
Eddy County, New Mexico

Gentlemen:

The following is a Deviation Survey for the above captioned well.

DEPTH	DEVIATION
358'	1°
895'	1 1/4°
1419'	1°
1915'	1°
2439'	3/4°
2905'	1°
3405'	1°
3927'	1 1/4°
4450'	1°

Very truly yours,

B. N. Muncy Jr.
Secretary

STATE OF NEW MEXICO §
COUNTY OF EDDY §

The foregoing was acknowledged before me this 30th day of April, 1986.

NOTARY PUBLIC

