

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

| | | | | | |
|-------------------------------------|---------------|--------------------------------------|--------------------|--------------------------------|--------------------|
| Operator <u>Hammid Petro. Corp.</u> | | Lease <u>Two Hills 33</u> | | Well # <u>44 33</u> | |
| Location of Well | Unit <u>P</u> | Section <u>14</u> | Township <u>19</u> | Range <u>27</u> | County <u>Eddy</u> |
| Drilling Contractor | <u>Rotary</u> | | Type of Equipment | | |

APPROVED CASING PROGRAM

| Size of Hole | Size of Casing | Weight Per Foot | New or Used | Depth | Sacks Cement |
|----------------|----------------|-----------------|-------------|--------------|---------------|
| <u>12 1/4"</u> | <u>8 5/8"</u> | <u>24 #</u> | <u>New</u> | <u>300'</u> | <u>200 sr</u> |
| <u>7 7/8"</u> | <u>4 1/2"</u> | <u>9.5</u> | <u>..</u> | <u>1900'</u> | <u>250 sr</u> |
| | | | | | |

Casing Data:

Surface _____ joints of 8 5/8" inch 24 # Grade J-55~~(Approved)~~ (Rejected) _____Inspected by M.G. date 9/25/86

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____Type of Shoe used None Float collar used insert Btm 3 jts welded yesTD of hole 316' Set 316' Feet of 8 5/8" inch 24 # Grade J-55New-used csg. @ 316' with 150 270-r sacks neat cement around shoe

+ _____ sax _____ additives _____

Plug down @ 2:00 (AM) (PM) Date 9/26/86Cement circulated yes No. of Sacks 24 srCemented by Donnell Witnessed by Mild Steelfield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

Wtr 125'-160'