

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN _____ LOCATE _____
(Other instructions on re-verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different zone. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	2. NAME OF OPERATOR Harvey E. Yates Company	3. ADDRESS OF OPERATOR P.O. Box 1933, Roswell, New Mexico 88202	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 990' FNL & 1980' FEL	5. LEASE DESIGNATION AND SERIAL NO. LC-062052	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	7. UNIT AGREEMENT NAME	8. FARM OR LEASE NAME Hudson 11 Federal	9. WELL NO. #3	10. FIELD AND POOL, OR WILDCAT Tamano Bone Spring	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 11, T18S, R31E	12. COUNTY OR PARISH Eddy	13. STATE N.M.
14. PERMIT NO. 30-015-25737	15. ELEVATIONS (Show whether OF, RT, GR, etc.) 3752.2 GL		16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data									

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐	WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐	FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐	SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☒
REPAIR WELL	☐	CHANGE PLANS	☐	(Other) Spud & csg notice			
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)							
17. (If well is being drilled or completed, clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)							

1/2/89 Spud well @ 12:01 am
TD @ 354', Ran 13 3/8 54.5 J-55 csg to 354'
Cemented w/350 sks Class "C" w/2% CaCl, Circ 36 sks to pit
WOC 12 hrs, Test csg & BOP to 600 psi/30 min - Held OK

1/5/89 TD 12 1/4" hole @ 2318'
Ran 8 5/8 32# J-55 csg to 2318'
Cemented w/1100 sks filler & 200 sks Class "C" w/2% CaCl,
Did not circ cmt, Ran Temperature Survey & found TOC @ 664',
GIH w/1" tbg to 664', Cemented w/300 sks Class "C", Circ 5 sks
to pit, WOC 12 hrs, Test csg & BOP to 1200 psi/30 min - Held OK.

ACCEPTED FOR RECORD

JAN 26 1989

E/B

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED A. M. Young NM Young TITLE Drilling Superintendent DATE 1/6/89

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

BENNETT-CATHEY WIRE LINE SERVICE
P. O. BOX 787 / ARTESIA, NEW MEXICO 88210 / PHONE 746-3281

TEMPERATURE SURVEY



OPERATOR HEYCO
LEASE HUDSON 11 FEDERAL
WELL NO. #3
COMPANY REPRESENTATIVE CURTIS TOLLES
DATE & TIME CEMENT JOB COMPLETED 1415 1-5-89
DATE & TIME SURVEY MADE 1900 HRS. 1-5-89
SURVEY RUN BY LARRY MOSSBARGER
WELL DATA INDICATION OF CEMENT TOP AT 600 FEET
TAG TD AT 2213 FEET

