

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-058709-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Taylor Deep 12 Federal

WELL NO.

#1-Y

10. FIELD AND POOL, OR WILDCAT

Wildcat - WOC 12

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 12, T-18S, R-31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Harvey E. Yates Company

3. ADDRESS OF OPERATOR

P.O. Box 1933, Roswell, NM 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

2235 FS & WL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3764.6

RECEIVED BY
JUN 15 1987
O. C. D.
ARTESIA, OFFICE

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Spud & Cement

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6/3/87 Spud well, TD @ 350', Ran 9 jts, 13 3/8, ST&C, 54.5# J55 csg, set @ 350', Cemented w/350 sks Class "C" w/2% CaCl₂.
Circ 34 sks to pit, Plug Down @ 11:45 pm 6/3/87, WOC 12 hrs
Test csg 600# for 30 min, Held-ok

6/6/87 T.D. @ 2410, Ran 58 jts 8 5/8, ST&C, 24# J55 csg, Set @ 2410
Cemented w/600 sks DLW III & 200 sks Class "C" w/2% CaCl₂.
Plug Down @ 10:30 pm 6/6/87. Did not circ. Temperature survey showed TOC @ 400'. Ran 1" pipe to 400' & pumped 148 sks Class "C". Circ 20 sks to surface. Released 1" pipe.
WOC 12 hrs. Test csg 1200# for 30 min. Held ok.
(NOTE: Temperature survey & cementing operations witnessed by Vince Balderaz)

ACCEPTED FOR RECORD

JUN 11 1987

SJS
CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

NM Young

TITLE Drilling Superintendent

DATE 6/8/87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side