

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Yates Pet Corp</u>			Lease <u>Dagger ZW</u>		Well # <u>1</u>
Location of Well	Unit <u>K</u>	Section <u>30</u>	Township <u>19</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor			Type of Equipment <u>Rotary</u>		

*

Witness

APPROVED CASING PROGRAM

*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 3/4</u>	<u>9 5/8</u>	<u>36 # J-55</u>		<u>1150</u>	<u>Circ 925SX</u>
<u>8 3/4</u>	<u>7</u>	<u>24# K-55+</u> <u>N-80</u> <u>23# K-55</u>		<u>8000</u>	<u>400 SX</u>

Casing Data:

Surface joints of 9 5/8" inch 36 # Grade J-55

(Approved) (Rejected)

Inspected by M.S. date 9/9/89

Cementing Program

Size of hole 14 3/4" Size of Casing 9 5/8" Sacks cement required Type of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 1125' Set 1125' Feet of 9 5/8" inch 36 # Grade J-55New used csg. @ 1125' with 1200 22# sacks neat cement around shoe+ sack additives Plug down @ 5:00 (AM) (PM) Date 9/10/89Cement circulated yes No. of Sacks 100 SXCemented by Western Company Witnessed by Michael StullTemp. Survey ran @ (AM) (PM) Date top cement @ Casing test @ (AM) (PM) Date Method Used Witnessed by Checked for shut off @ (AM) (PM) Date Method used Witnessed by Remarks:

Last returns 2924' required

No artulizers or breakers ran.

Last only level 2 730'