

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

AUG 19 '88

O. C. D.

ARTESIA OFFICE

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Dagger ZW
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER K 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 30 TOWNSHIP 19S RANGE 25E NMPM.	10. Field and Pool, or Wildcat N. Dagger Draw Upper Penn
15. Elevation (Show whether DF, RT, GR, etc.) 3564' GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

Cement squeeze to shut off water. ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

WIH with wireline and set retainer 7768'. WIH w/tubing. Stung into retainer. Pumped 45 bbls water at 3 BPM @300 psi. Blow on annulus. Pulled out of retainer. Pumped 2000 gals Tembloc 75. Displaced w/45 bbls water. No returns on annulus. Cement squeezed perforations 7779-93' and 7834-35' w/150 sx Class "C" with fluid loss additive. POOH. Tagged cement at 7588'. Drilled to 7603'. Circulate down to 7693'. Tagged cement. Drilled to 7765'. Circulate hole clean. Return well to production 8-5-88.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Juanita S. Sackett TITLE Production Supervisor DATE 8-18-88

Original Signed By
Mike Williams

DATE AUG 23 1988

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY: