

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029392 B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hinkle "B" Federal

9. WELL NO.

20

10. FIELD AND POOL, OR WILDCAT

Shugart Y-SR-06

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 27, T18S R31E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1. OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

Westall-Mask

3. ADDRESS OF OPERATOR

P.O. Drawer 1477 Roswell, N.M. 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

2310 FSL and 2310" FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

36 31 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 11-10-87 the following work was performed

Started Pumping to much water

On 1-5-88 Pulled rods and tubing and ran packer and plug
straddled lower zone and swabbed. Swabbed dry, repeated on middle zone.
To much water repeated on Top zone. It seems ok ran past iron plug
to 3655' and put on pump

On 2-15-88 the following work was performed

Pulled rods and tubing ran plug (castiron) and set at 3,000'
Perforated 17 holes - 2530 32-34-40-42-44-2604-06-08-16-18-20-22-24, 2698-2700-2702

On 2-16-88 the following work was performed:

Fracture using 42,000 gal water, 45,000 # 20/40 sand 16,000# of 12/20 sand (curable)

On 3-3-88 the following work was performed: Acidized with 3,000 Gal 10%
swabbed and put back on pump. 2 3/8 tubing at 2575'

18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

SJS