AM I SCION

Form 9-331 Dec. 1973

RECEIVED

Form Approved.

DEPARTMENT GEOLOGI	OF	THE	INTER	lOR,
GEOL()GI	CAL	SUR	VFY	NO:

(Do not use this form for proposals to drill or to deeper or plug back to a different reservoir. Use Form 9–331–C for such proposals.)

SUNDRY NOTICES AND REPORTS

	Budg	et Bureau No. 42-R1424
H j	5. LEASE	
LS ifferent	PENNIT AGREEMENT N	AME
	8. FARM OR LEASE NAM Walters Federal	1E
	9. WELL NO.	
	10. FIELD OR WILDCAT N Undes McMillan U.	AME Penn(Gas)
ce 17	11. SEC., T., R., M., OR B AREA Sec. 7, T19S, R27	LK. AND SURVEY OR
TICE,	12. COUNTY OR PARISH Eddy 14. API NO.	13. STATE
IICE,	15. ELEVATIONS (SHOW 3271' GL	DF, KDB, AND WD)

1. oil gas well \boxtimes well other 2. NAME OF OPERATOR Robert N. Enfield . TESIA OFFICE 3. ADDRESS OF OPERATOR P.O. Box 2431, Santa Fe, NM 87501 4. LOCATION OF WELL (REFORT LOCATION CLEARLY, See space 17 below.) 1980' FNL & 990' FEL of Sec. 7 AT SURFĀĆE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BCX TO INDICATE NATURE OF NOTICE,

REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Spub Dany Donling SET 13-35

SUBSEQUENT REPORT OF:

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 17-1/2" hole 9:30 AM, drilled to 320'KB. Set 7 jts. 13-3/8" 10/20/87 61# K-55 casing at 317.45 KB. Cemented w/350 sx Class C w/2% CaC12. 25 sx circulated to pit, plug down 5 PM 10/19/87. Witnessed by Danny Cortez, BLM, Carlsbad. Deviation 320 1°.

10/21/87 Drilling at 965'. Deviation 569' 1/2°, 871' 3/4°. Pressure tested 13-3/8" casing to 1000# for 30 min., held 0K

Drilling at 1570'. Deviation 1120' 1-1/4°, 1457' 1/2°. 10/22/87

10/23/87 Drilling at 2195'. Deviation 1730' 1-1/2°, 1980' 1-1/4°.

Subsurface Safety Valve: Manu, and Type	
	· · · Set @ Ft.
18. I hereby certify that the foregoing is true and correct	11 (00 (07

SIGNED / aby 11- 25 felle TITI Sperator

11/03/87

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

_ TI LE ._..__

รฉร PISBAD, NEW MEXICO