

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO

NM-0560353

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hale 11 Federal

9. WELL NO.

#2

10. FIELD AND POOL, OR WILDCAT

Benson Bone Spring

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 11, T19S, R30E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Harvey E. Yates Company

3. ADDRESS OF OPERATOR

P.O. Box 1933, Roswell, New Mexico 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

2130' FEL & 1980' FSL

14. PERMIT NO

30-015-25832

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3364.4 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud & csg report

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

1/21/88 Spud well, TD @ 360 ft  
Ran 362' of 13 3/8, 54.5# csg, Set @ 360 ft  
Cemented w/400 sks w/2% CaCl2 & 1/4# Celloflake, Circ 80 sks to pit  
WOC-12 hrs, Test BOP-600 psi/30 min-Held ok

1/24/88 TD 11" @ 2040 ft  
Ran 2044 ft 8 5/8, 24# csg, Set @ 2040  
Cemented w/1000 sks filler & 200 sks "C" w/2% CaCl2 & 1/4# celloflake  
Circ 180 sks to pit, WOC 12 hrs, Test BOP-1200 psi/30 min-Held ok

18. I hereby certify that the foregoing is true and correct

SIGNED

NM Young

TITLE Drilling Superintendent

DATE Jan 26, 1988

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 1 1988

\*See Instructions on Reverse Side

SJS  
CARLSBAD, NEW MEXICO