

SIETE OIL & GAS CORPORATION

WELL: Nugget State No. 1
 FIELD: Undesignated Delaware
 Lease #: V-736
 Spud: 11-18-87

LOCATION:
 660' FML & 660' FEL
 Section 36, T-19S, R-31E
 Eddy County, N.M.

Note: All tested intervals are Delaware

PRESENT WELLBORE

ELEVATION: 3510' KB

ZERO: 8' AGL

TOPS

 Rustler - 937'
 T/Salt - 937'
 B/Salt - 2445'
 Yates - 2569'
 Del. Sand - 4280'
 Bone Spring - 7230'

> 13-3/8", 54#/ft set @ 600' w/
 315 sxs 65/35 POZ, 6% D-20, 2% salt, &
 1/4#/sk D-29, tail w/ 200 sxs. HE11
 w/ 2% salt & 1/4#/sk D-29
 Tail w/ 200 sxs HE-11 w/ 2% salt & 1/4# D-29
 circ, 50 sxs

Note: 13-3/8" - 8-5/8"
 annulus 1" to surface
 w/ 200 sxs Class C.

> 8-5/8" 24# & 28 # J-55 casing set @ 3750'
 w/ 400 sxs, 35/65 POZ, 6% D-20, 8% salt,
 & 1/4# D-29, Tail in w/ 200 sxs Standard

PRESENT COMPLETION INTERVAL

2-3/8", 4.7 #/ft
 8nd tbg w/ PKR @ 6455'

CIBP 6910'-----

< Perf Run #3, 4470-4486.5 (12 perfs)
 < acid 500 gals 15% HCL, frac w/ 18,000 gals 45,000# sd

< Perf Run #2, 5636-47 (12 shots)
 < acid 1000 gals, Frac 18,000 gals & 43,000 # sd

< Perf Run #4, 6493'-6503' (11 shots) w/1000 gals 15 % HCL
 < Fraced w/ 9500 gals 30# XL & 13,200# sand

< Perf Run #7, 6919'-6931' (11 shots) w/500 gals 15 % HCL

< Perf Run #6, 6990'-6996' (7 shots) w/500 gals 15 % HCL

< Perf Run #5, 7040-7050 (11 shots)
 < acid 750 gals, 15% HCL

< Perf Run #1, 7071-7082 (12 shots)
 < acid 1000 gals, Frac w/ 22,000 gals w/ 31,000 # sd

< - 5-1/2" & 17# LT&C Casing @ 7324'
 DV tool @ 4292' omt 1st stage w/ 775 sxs
 TD: 7327' 2nd stage 550 sxs 35/65 POZA circ. 40 sxs