

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

NOV 25 '88

O. C. D.
SANTA FE, OFFICE

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Siete Oil & Gas Corporation	8. Farm or Lease Name Nugget State
3. Address of Operator P.O. Box 2523 Roswell, NM 88202-2523	9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> , <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>19S</u> RANGE <u>31E</u> NMPM.	10. Field and Pool, or Wildcat South Lusk Delaware
15. Elevation (Show whether DF, RT, GR, etc.) 3510' KB 3502' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Siete Oil & Gas Corporation proposes to plug & abandon the Nugget Federal No. 1 as follows:
(Note: Refer to attached wellbore diagrams)

- 35' Cml on Top of CIBPC 6910
- POOH w/production equipment.
- Set CIBP @ 4450' 4380
- Circ hole 9.0# salt gel.
- Spot 175 sks cement on CIBP @ 4450' 4380 Top Delaware 4280
- Spot 100' cement plugs as follows: (min 25 sk)
- a. 3700'-3800'
- b. 2450'-2550' - 100' plug 975-875-Top Salt
- * c. 550'-650'
- Spot 50' cement plug from 50' to surface.
- RD, erect P&A marker & clean location.

Last production test: 11/18/88 - 3 BO & 32 BW.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. E. Roach TITLE Production/Reservoir Engineer DATE 11/22/88

APPROVED BY Mike Williams TITLE Plugging DATE DEC 5 1988

CONDITIONS OF APPROVAL, IF ANY: As Noted Above