

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a dry well.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

FEB 17 '88

O. C. D.
ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO

NM 2537

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

South Taylor 13 Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

East Shugart Delaware

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec. 13, T18S, R31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, CR, etc.)

3715.2 GL

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☒
☒

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1-17-88 Drill out to 5410'.

1-19-88 Perforate Delaware 5380-90' (2 JSPF - 21 holes). Spot 250 gals 7 1/2% HCI followed w/2250 gals same & RCN BS.

1-20-88 Frac Delaware perfs 5380-90' w/15,000 gals YF3G, 3000#, 100 mesh sand & 28,000# 16-30 ottawa.

1-22-88 Run tbg., pump and rod. WO pump jack and electricity.

1-23-88 Put on production @ 4:00 PM

2-5-88 Perf. Delaware @ 5310-30' (20' - 2 JSPF, 41 holes). Spot 250 gal 7 1/2% SRA across perfs & break down. Follow w/2750 gals 7 1/2% SRA & ball sealers.

2-6-88 Frac w/20,000 gals YF 130G & 40,500 sand (3300# 100 mesh & 37,200# 16-30 ottawa).

2-8-88 Put on pump. (Anchor @ 4775', SN @ 5085).

ACCEPTED FOR RECORD

FEB 11 1988

SJS
CAPITOLAD, NEW MEXICO

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Production Manager/Engineer

DATE

February 9, 1988

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

1911

1912

1913