	UN TED STATES Dr ARTME. OF THE INTE	ing and ". will made of the	5. LEAD	xpires August E DESIGNATION IM 26864	31. 1985 C	
SUNDRY N	NOTICES AND REPORTS proponais to drill or to deepen or plu PLICATION FOR PERMIT—" for such	REVENELS		NDIAN, ALLOTTEE	OR TRIBE NAME	
I. GAB WELL GAB OTE		JAN 19 '88	7. 01	F AGREEMENT NA		
2. NAME OF OPERATOR		8. FARI	8. FARM OR LEASE NAME Roden GD Federal Com 9. WBLL NO. 2 10. FIBLD AND FOOL, OR WILDCAT			
Yates Petroleum Corporation (D. C. D.						
3. ADDRESS OF OFERATOR 105 South 4th St., Artesia, NM 88210						
 LOCATION OF WELL (Report location clearly and in accordance with any State requirements." See also space 17 below.) At surface 1980' FSL & 1980' FWL 						
			Penn Und. No. Dagger Draw Upper 11. BHC. T. E. M., OF BLE. AND SURVEY OF AREA Unit K, Sec. 25-T19S-R24E			
14. PERMIT NO.	15. BLEVATIONS (Show whether	DF. RT. GR. etc.)		K, SEC. Z		
PI # 30-015-25852	3616'	GR		dy	NM	
16. Chec	k Appropriate Box To Indicate	Nature of Notice. Report	or Other De	ata .	<u> </u>	
	INTENTION TO :		ABQUENT REPO			
TEST WATER SHUT-OFF	PELL OR ALTER CASING	WATER SHUT-OFF	XX	REPAIRING W	BLL	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT		ALTERING CA	BING	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING		ABANDONMEN	T*	
REPAIR WELL	CHANGE PLANS	(Other)	ults of multi	-1		
Spudded 26" hole 9 Resumed drilling 1	DOPERATIONS (Clearly state all pertin irectionally drilled, give subsurface to 9:00 AM 12-29-87. Set 14-3/4" hole 3:30 PM 1	40" of 20" conducto 2-31-87 with rotary.	ompletion Rep ates, including ertical depths or pipe.	oort and Log form g estimated date for all markers	m.) of starting any and gones perti-	
 DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Spudded 26" hole 9 Resumed drilling 1 Ran 29 joints 9-5/ shoe set 1212'. F1 10# Gilsonite, 1/2 w/200 sx Premium H 1-2-88. Bumped p1 not circulate. WC Ran 1". Tagged ce out 2:00 AM 1-4-88 Resumed drilling. 	9:00 AM 12-29-87. Set	40' of 20" conducto 2-31-87 with rotary. ng set 1212'. Texa Cemented w/400 sx aCl (yield 1.99, wei (yield 1.32, weight ed pressure and floa ture Survey and foun d 1489 sx Class "C" minutes. NU and tes	ompletion Beg ates, including er pipe. s Patter Hallibur ght 12.4 14.8). t held o d top of with 4% ted. Re	n Notched ton Lite to). Tailed PD 5:30 1 kay. Ceme cement 60 CaCl. W00 duced hold	m.) of starting any and gones perti- with d in PM ent did DO'. C. Drilled	
 17. DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Spudded 26" hole 9 Resumed drilling 1 Ran 29 joints 9-5/ shoe set 1212'. F1 10# Gilsonite, 1/2 w/200 sx Premium H 1-2-88. Bumped p1 not circulate. WC Ran 1". Tagged ce out 2:00 AM 1-4-88 Resumed drilling. 	Anectionally drilled, give subsurface to 9:00 AM 12-29-87. Set 14-3/4" hole 3:30 PM 1 /8" 36# J-55 ST&C casi: loat collar set 1168'. 2#/sx Flocele and 3% C. Plus "C" with 2% CaCl2 lug to 500 psi, release OC 6 hrs. Ran Tempera ement at 416'. Spotter 3. WOC 32 hrs and 30 m Witnessed by Dale Casi cement to surface.	40' of 20" conducto 2-31-87 with rotary. ng set 1212'. Texa Cemented w/400 sx aCl (yield 1.99, wei (yield 1.32, weight ed pressure and floa ture Survey and foun d 1489 sx Class "C" minutes. NU and tes	r pipe. s Patter Hallibur ght 12.4 14.8). t held o d top of with 4% ted. Re and Mana r	ATE	m.) of starting any and gones perti- guide with d in PM ent did DO'. C. Drilled e to 8-3/4".	
 I. DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Spudded 26" hole 9 Resumed drilling 1 Ran 29 joints 9-57 shoe set 1212'. FI 10# Gilsonite, 1/2 w/200 sx Premium H 1-2-88. Bumped p1 not circulate. W(Ran 1". Tagged ce out 2:00 AM 1-4-88 Resumed drilling. Note: Circulated Note: Circulated Note: Circulated SIGNED	Anectionally drilled, give subsurface to 9:00 AM 12-29-87. Set 14-3/4" hole 3:30 PM 1 /8" 36# J-55 ST&C casi: loat collar set 1168'. 2#/sx Flocele and 3% C. Plus "C" with 2% CaCl2 lug to 500 psi, release OC 6 hrs. Ran Tempera ement at 416'. Spotter 3. WOC 32 hrs and 30 m Witnessed by Dale Casi cement to surface.	40' of 20" conducto 2-31-87 with rotary. ng set 1212'. Texa Cemented w/400 sx aCl (yield 1.99, wei (yield 1.32, weight ed pressure and floa ture Survey and foun d 1489 sx Class "C" minutes. NU and tes rpenter, Bureau of L	r pipe. s Patter Hallibur ght 12.4 14.8). t held o d top of with 4% ted. Re and Mana r	n Notched ton Lite to). Tailed PD 5:30 l kay. Ceme cement 60 duced hold gement.	m.) of starting any and sones perti- guide with d in PM ent did DO'. C. Drilled e to 8-3/4".	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.