

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OFFICE FOR MANAGEMENT
OF COPIES REQUIRED
FOR THE INSTRUCTIONS
ON THE REVERSE SIDE

Modified Form No.
NM60-3160-4

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐ Workover

2. NAME OF OPERATOR
YATES PETROLEUM CORPORATION

3a. Area Code & Phone No.
505/748-1471

3. ADDRESS OF OPERATOR
105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL, 660' FWL, Sec. 20-19S-25E

14. PERMIT NO.
30-015-25903

15. ELEVATION (Show whether DF, RT, GR, etc.)
3580.8' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 0557142

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

7. UNIT AGREEMENT NAME

N/A

8. FARM OR LEASE NAME

Ross EG Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

North Dagger Draw Upper Penn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit D, Sec. 20-T19S-R25E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Add additional perforations

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANE

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Propose to perforate additional Canyon as follows: 7912, 14, 15 (2 SPF-6 holes: 7888, 91, 92 (2 SPF-6 holes), 7867, 69, 71, 76 (2 SPF-8 holes) and 7835, 37 (2 SPF-4 holes) total 24 holes. Acidize in three stages with 1200 gals 20% HCL acid + balls. Swab back and evaluate.

Set RBP @ \pm 7930'. Set tubing open-ended @ 7730'. Treat down tubing and casing (triple entry) with 20000 gals 20% HCL + 900# block in 10# gelled brine.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Supervisor

DATE 3-18-91

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

4/4/91

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side