

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
T. Salt _____
D. Salt _____
T. Yates _____
T. 7 Rivers _____
T. Queen _____
T. Grayburg _____
T. San Andres _____
T. Glorieta _____ 1970
T. Paddock _____
T. Blinberry _____
T. Tubb _____
T. Drinkard _____
T. Abo _____ Shale 4108
T. Wolfcamp _____ 5456
T. Penn. _____
T. Cisco (Bough C) _____ 6714

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todillo _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn. "A" _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
No. 2, from _____ to _____
No. 3, from _____ to _____
No. 4, from _____ to _____
No. 5, from _____ to _____
No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
No. 2, from _____ to _____ feet
No. 3, from _____ to _____ feet
No. 4, from _____ to _____ feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	50	50	Surface, Rock	5446	7040	1594	Lm, Sh
50	515	465	Redbeds, Anhy	7040	7620	580	Sd, Lm, Sh
515	925	410	Anhy, Sd	7620	8038	418	Ls, Sh
925	1175	250	Anhy				
1175	1540	365	Dolo, Anhy, Cht, Sh				
1540	1964	424	Dolo				
1964	2130	166	Dolo, Sd, Lm				
2130	2300	170	Dolo, Sd, Sh				
2300	2710	410	Dolo				
2710	2960	250	Dolo, Sd				
2960	3408	448	Dolo				
3408	3710	302	Dolo, LS, Sh				
3710	4060	350	Dolo, Sh				
4060	4440	380	Dolo, Lm, Sh				
4440	5446	1006	Dolo				