

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	☒

OIL CONSERVATION DIVISION
P. O. BOX 2068
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

RECEIVED

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER		7. Unit Agreement Name
2. Name of Operator NEARBURG PRODUCING COMPANY		8. Form or Lease Name ROSE 12A
3. Address of Operator P.O. BOX 31405, Dallas, Texas 75231		9. Well No. 1
4. Location of Well UNIT LETTER A 990 FEET FROM THE NORTH LINE AND 990 FEET FROM EAST 12 TOWNSHIP 19S RANGE 25E		10. Field and Pool, or Wildcat UND. BOYD MORROW
11. Elevation (Show whether DF, RT, GR, etc.) 3391.9 GR.		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPER. ☒
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1702.

- 9/30/88: SPUD @ 2:30pm (MST). DRILLED 17 1/2" hole to 350'. Reduced hole size to 12 1/4" and drilled to 1350'.
- 10/2/88: Ran 34 Joints 8 5/8" 24# casing, set @ 1350. Cemented with 750 sx HOWCO LITE w/ 2% Ca.Cl, 300sx Thick -set w/10# Gilsonite per sx & 1% Ca.Cl. Tailed in with 200sx premium plus & 2% Ca. Cl. Plug down @ 6:45am Circulated 180sx to Pit. Held 1,000# For 30 minutes. W.O.C. 18 hours. Drilled 7 7/8" hole to 9345'.
- 10/25/88: Ran open hole Logs to 9345'.
- 10/28/88: Ran 248 Jts. of 4 1/2, 11.60 # casing, set @ 9342'. Cemented with 475sx class (H) with 5# KCL per sx, .3% CFR-3, and .3% HALAD 22A. Plug down @ 6:50am 10/28/88. Held 1,000 P.S.I. For 30 minutes, Released & Plug Held. Temperature Survey indicated top of cement at 7800; out side 4 1/2" casing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Eddie J. Schuch TITLE Operations Coordinator DATE 11/4/88

Original Signed By Mike Williams DATE NOV 14 1988

CONDITIONS OF APPROVAL, IF ANY: