FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator Joh	Lease Schoonmaker Si.				Well # 4			
Location of Well	Unit L	Unit Section		Township		Ronge 29	County Eddy	
Drilling Contractor Contractor								
APPROVED CASING PROGRAM								
Size of Hole	Size	of Casing	Weigl Foo		Nev	v or Used	Depth	Sacks Coment
15 ''	103/	4 ¹¹					300'	circ.
10"	<i>"</i> η"						1210	ש ב
6 1/2"	41/2	."					3000'	1200'
Casing Data:				· · · · · · · · · · · · · · · · · · ·			3000	1 2200
Surfacejoints ofinch# Grade								
(Approved) (Rejected)								
Inspected by date								
Cementing Program								
Size of hole 10"								
Type of Shoe used quide Float collar used NO Btm 3 jts welded yes								
TD of hole 1230' Set 1230' Feet of 7' Inch 20 # Grade J-55								
New-used csg. @ 1230 with 200 sacks near cement around shoe								
+ 200 sax Hall, Lite additives (15# sult/sy)								
Plug down @ <u>2300</u> (AM) (M) Date <u>1-20-89</u>								
Cement circulated Ves No. of Sacks 100								
Cemented by Halliburton Witnessed by Mike Stubblefield								
Temp. Survey ran @ (AM) (PM) Datetop cement @ Casing test @(AM) (PM) Date								
Casing test @		(AM) (P)	vi) Dat	e				
Nethod Used Witnessed by								
checked for shut off ((AM) (PM) · Date								
Method usedWitnessed by								
Remarks:								
	•							
						·····	·····	