

DEPARTMENT OF THE INTERIOR
BUREAU LAND MANAGEMENT

(Other Instructions on Reverse Side)

LEASE DESIGNATION AND SERIAL

NM-025777

IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☒ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
Siete Oil and Gas Corporation

3. ADDRESS OF OPERATOR
P. O. Box 2523 Roswell, New Mexico 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
790' FNL & 1650' FEL
Unit Letter B

14. PERMIT NO.
API # - 30-015-26022

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3722' GR

JAN 9 9 00 AM '89
CARLSBAD AREA
RECEIVED
FEB 1 '89
O. C. D.
ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Geronimo Federal

9. WELL NO.
12

10. FIELD AND POOL OR WILDCAT
Shugart Delaware

11. SEC., T., B., M., OR B.L. AND SURVEY OR AREA
Sec. 24: T18S, R31E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) ☒ Production Casing ☒
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1/3/89 Set 908.06' 17# N-80, 965.17' 17# JE 42 & 3748.26' 15.50# J-55
LT & C 5 1/2" casing - 5621.59'. Set @ 5600'. Cement in 2 stages
w/ stage collar @ 3611'.
1st stage - cement w/370 sks. Tail End Standard w/.7% D-127 Fla and
10% salt (BWOW).
2nd stage - cement w/800 sks. 35/65 POZA, 6% gel, 10% salt (BWOW)
and 1/4# sk. flakes. Circulate 60 sks. to pits.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production/Reservoir Engineer DATE 1/6/89

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAN 30 1989

*See Instructions on Reverse Side

SCS
CARLSBAD, NEW MEXICO