BUREAU OF LAND MANAGEMENT

NM-24160

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

C/SF

RECEIVED

FEB 16 '90

O. C. D. ARTESIA, OFFICE

Gas Well [X] Other Well [ ] Other

Name of Operator: Siete Oil & Gas Corporation

Address of Operator: P.O. Box 2523 Roswell, NM 88202-2523

Location of Well (Report location clearly and in accordance with any State requirements. See also space 17 below.): 1980' FSL & 760' FWL, NW¼SW¼, Unit Letter L

Lease Name: Osage Federal

Well No.: 5

Field and Pool, or Wildcat: Parkway Delaware

Sec., T., R., M., or Blk. and Survey or Area: Sec. 35: T19S, R29E

API Number: 30-015-26029

Elevations (Show whether DF, RT, GR, etc.): 3319' GR

County or Parish: Eddy

State: NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

Notice of Intention to:				Subsequent Report of:			
Test Water Shut-Off	[ ]	Pull or Alter Casing	[ ]	Water Shut-Off	[ ]	Repairing Well	[ ]
Fracture Treat	[ ]	Multiple Complete	[ ]	Fracture Treatment	[ ]	Altering Casing	[ ]
Shoot or Acidize	[ ]	Abandon*	[ ]	Shooting or Acidizing	[ ]	Abandonment*	[ ]
Repair Well	[ ]	Change Plans	[ ]	(Other) Inter. Csg, TD, Prod. Csg			[X]
(Other)				(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/13/88 TD 12¼" hole to 3200' @ 6:30 PM, RU & ran 75 jts (3204') 8 5/8" 24# J-55 csg, set @ 3200' w/100 sks 35/65 POZA + additives, 500 sks 35/65 POZ + additives, tail-in w/200 sks HEII + additives, PD @ 2:45 AM on 12/14/88, 1" cement to surface.

12/15/88 Tested BOP to 1000#, held ok, DO @ 5:00 PM.

12/17/88 TD 7 7/8" hole to 5000' @ 8:00 PM, RU Schlumberger & ran CNL/LDT, DLL/MSFL, EPT & Volan, logger's TD @ 5000'.

12/18/88 RU & ran 121 jts (5008') 5½" 15.5# J-55 csg, set @ 5000' w/450 sks tail-in Std + additives, PD @ 11:15 PM, released L&M Rig #1 @ 12:15 AM on 12/19/88.

CONFIDENTIAL

RECEIVED JAN 3 11 55 AM '89 CARLSBAD, NM

18. I hereby certify that the foregoing is true and correct

SIGNED Cathy C. Bailey TITLE Drilling & Production Secretary DATE 12/27/88

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

JAN 13 1989

SJS

CARLSBAD, NEW MEXICO

*See Instructions on Reverse Side