

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

FEB 16 '89
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-26047

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

V-1116

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter J : 1980 Feet From The South Line and 2230 Feet From The East Line

Section 2 Township 20S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3640.1' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole at 8:00 AM 2-1-89. Set 40' of 20" conductor pipe. Notified NMOCD, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 8:00 PM 2-3-89. Lost returns 200'. Had 50% returns 208' and 100% returns at 216'. Ran 29 joints 9-5/8" 36# J-55 ST&C casing set 1217'. Texas Pattern Notched guide shoe set 1217'. insert float set 1175'. Cemented w/500 gals Surebond, 725 sx Pacesetter "C" Lite with 1/4#/sx Celloseal, 5#/sx Gilsonite + 3% CaCl2 (yield 1.84, weight 12.7). Tailed in w/200 sx Class "C" + 2% CaCl2 (yield 1.32, weight 14.8). PD 3:15 AM 2-7-89. Plug did not bump. Float held okay. Cement circulated 50 sacks to pit. WOC. Drilled out 2:00 AM 2-8-89. WOC 22 hrs and 45 minutes. NU and tesetd to 1000 psi for 30 minutes, OK. Reduced hole to 8-3/4". Drilled plug (tag plug 1175') and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 2-14-89

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

Original Signed By

Mike Williams

FEB 16 1989

APPROVED BY Mike Williams TITLE Production Supervisor DATE 2-14-89

CONDITIONS OF APPROVAL, IF ANY: