FIELD REPORT FOR CEMENTING OF WELLS

,

OIL CONSERVATION DIVISION

.

.

Operator Morexco Inc			Lease Mary Wolf State			Well # 4		
Location of Well		Section		Township 19			County Eddy	
Drilling Contractor United Drilling Type of Equipment Rotary								
* Witn	255	APPROVE	ED CASI	NG PROG	GRAM			
Size of Hole	Size of	Casing	Weigh Foo		New	or Used	Depth	Sacks Cement
121/4	* 85/	8	24	#_			320	300
7 7/8	7718 51/2		10,5-15,5#		:		2400	450
Casing Data: Surface	joints of		ach .		Spad	Α		
Surfacejoints ofinch# Grade (Approved) (Rejected)								
Inspected bydate								
Cementing Program								
Size of hole 121/4" Size of Casing 85/8" Sacks coment required								
Type of Shoe used guide Float collar used insert Btm 3 jts welded yes								
TD of hole 365' Set 365' Feet of 85/8"Inch 24 # Grade J-55								
New used csg. @ 365' with 310 2% sacks neat cement around shoe								
+saxadditives Plug down @ 9:00 (AM) (PM) Date1-14-89								
Plug down @ <u>9°00</u> (AM) (PM) Date <u>11-14-89</u> Cement circulated <u>No</u> No. of Sacks <u>-O-</u>								
Cemented by Western Company Witnessed by Mike Gulfleliels								
Temp. Survey ran @ (AM) (PM) Date top cement @								
Casing test @(AN) (PN) Date								
Nethod Used Witnessed by								
Checked for s						, -		
		and the second distance of the second se				by		
Remarks: X Bo								
	ment was	•	/					
•					1			
	eady mixed		ce USII	29-44	<u>as</u> [egaymi		
l centralizer	<u>2 280'</u>						Wal	er) 190'

13