Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

Revised 1-1-89

OIL CONSERVATION DIVISION DISTRICT WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-015-26062 Santa Fe, New Mexico 87504-2088 P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease FEE STATE 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. VB-298 SUNDRY NOTICES AND REPORTS ON WELLS. ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN ON PLUTE HADE TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: FEB 23'89 Foothills AGH State WELL OTHER Name of Operator 8. Well No. O. J. Yates Petroleum Corporation 3. Address of Operator 9. Pool name/or Windows 105 South 4th St., Artesia, NM 88210 Undesignated Morrow 4. Well Location 0 : 660 Feet From The \_\_\_ South Line and 2310 Feet From The East Line 19S 23E Township Range **NMPM** Eddy County Section 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4046.4' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **CHANGE PLANS** PLUG AND ABANDONMENT **TEMPORARILY ABANDON** COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JOB **PULL OR ALTER CASING** OTHER: Intermediate casing XX OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 2-15-89. Ran 38 jts 8-5/8" 24# J-55 casing set 1630'. Texas Pattern Notched guide shoe set 1630', insert float 1588'. Cemented w/1000 gals Flocheck, 600 sx Halliburton Lite w/10#/sx Gilsonite, 1/2#/sx Floseal, 3% CaCl2 (yield 1.99, weight 12.7). Tailed in w/200 sx Class C with 2% CaCl2 (yield 1.32, weight 14.8). PD 7:15 AM 2-15-89. Bumped plug to 600 psi, float held okay. Cement did not circulate. WOC 6 hrs. Ran Temp. Survey and found top of cement 300'. Ran 1". Tag cement 318'. Spot 150 sx Class C with 4% CaCl2. Circulate 10 sacks to pit. PD 3:45 PM 2-15-89. WOC. NU and tested, held okay. Reduced hole to 7-7/8". Drilled out 1:15 AM 2-16-89. WOC 18 hours. Resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. TIME Production Supervisor \_ DATE \_\_2-22-89 Juanita Goodlett TELEPHONE NO. 505/748-1471TYPE OR PRINT NAME (This space for State Use) Original Signed By FEB 2 8 1989

APPROVED BY-

Mike Williams