

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

NOV 16 1989

A. C. D.
ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐

GAS WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter F : 1980 Feet From The North Line and 1980 Feet From The West Line

Section 2 Township 20S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3658' GR

WELL API NO.

30-015-26115

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

K-6385

7. Lease Name or Unit Agreement Name

Catclaw AGM State Com

8. Well No.

1

9. Pool name or Wildcat

Und. Cemetery Morrow

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 2:15 PM 11-3-89. Set 40' of 20" conductor. Notified, NMOC, Artesia, NM of spud. Ran 28 joints 10-3/4" 40.5# K-55 casing set 1210'. Guide shoe set 1210', insert float set 1166'. Cemented w/700 sx Pacesetter Lite w/10%/sx Hyseal, 1/2#/sx Celloseal and 3% CaCl2 (yield 1.80, wt 12.7). Followed w/200 sx Class C w/2% CaCl2 (yield 1.32, wt 14.8). PD 2:45 PM 11-10-89. Bumped plug to 800 psi, float held okay. Cement circulated 75 sacks. WOC. Drilled out 8:45 AM 11-11-89. WOC 18 hrs. NU and tested to 3000 psi for 30 minutes. Reduced hole to 9-1/2". Drilled plug and resumed drilling.

NOTE: Change of hole size from 8-3/4"
to 9-1/2"

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 11-13-89

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE NOV 28 1989

CONDITIONS OF APPROVAL, IF ANY: