

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DEC 20 '89

WELL API NO. 30-015-26118
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Parish IV Com
8. Well No. 2
9. Pool name or Wildcat Und. Hoag Tank Morrow
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3640' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Well Location Unit Letter F : 1980 Feet From The North Line and 1980 Feet From The West Line Section 26 Township 19S Range 24E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3640' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 9:45 AM 12-10-89. Set 40' of 20" conductor. Resumed drilling 14-3/4" hole 6:30 PM 12-15-89. Notified Mike Stubblefield, NMOCD, of spud and drilling with rotary. Lost circulation 280'. Drilling dry. Ran 28 joints 9-5/8" 36# J-55 casing, set 1290'. Guide shoe set 1290', insert float set 1244'. Cemented w/900 sx Halliburton Lite w/10#/sx gilsonite, 1/2#/sx flocele and 3% CaCl2 (yield 1.8, wt 12.6). Followed w/200 sx Class C w/2% CaCl2 (yield 1.32, wt 14.8). PD 9:15 AM 12-18-89. Cement did not circulate. Set cement basket at 644' and 322'. WOC 4 hrs. Ran Temperature Survey and found TOC 250'. Ran 1". Tagged cement 218'. Spotted 275 sx Class C w/4% CaCl. PD 2:30 PM 12-18-89. WOC 18 hrs. Drilled out 3:15 AM 12-19-89. NU and tested to 1000 psi. Reduced hole to 8-3/8". Drilled plug and cement.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 12-19-89
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

DEC 26 1989