o Appror≓ate ⊋istrict Office	Energy, erals and Natural R	exico lesources Department	C S Form C-103 Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION		WELL API NO.
DISTRICT II P.O. Drawer DD, Artesia, NM 88210 DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410 OEC 16 '96		30-015-26118 5. Indicate Type of Lease	
		ner 16 '96	6. State Oil & Gas Lease No.
	OTICES AND REPORTS ON WE		
(DO NOT USE THIS FORM FOR DIFFERENT RE (FOR	PROPOSALS TO DRILL OR TO DEEPEN SERVOIR. USE "APPLICATION FOR PE M C-101) FOR SUCH PROPOSALS.)	N OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
. Type of Well: OR. GAS WELL WELL	X OTHER		Parish IV Com
Name of Operator YATES PETROLEUM CORE	PORATION		8. Well No.
Address of Operator			9. Pool name or Wildcat
105 South 4th St., A	Artesia, NM 88210		Undesignated Strawn
Image: Neuropean line F	1980 Feet From The North Township 195 R	Range 24E	0 Feet From The West Line NMPM Eddy County
)' GR	
	ck Appropriate Box to Indicate		Report, or Other Data BSEQUENT REPORT OF:
Ļ.	INTENTION TO:		
		REMEDIAL WORK	
	_ CHANGE PLANS	COMMENCE DRILLIN	
		CASING TEST AND C	
DTHER:	LJ	OTHER: Squeeze	Canyon perfs X
 Describe Proposed or Completed (work) SEE RULE 1103. 	Dperations (Clearly state all pertinent details,	and give pertinent dates, incl	uding estimated date of starting any proposed
work) SEE RULE 1103. 12-3-96 - Moved in get pump to unseat wrapped around lon 12-4-96 - Work rod standing valve in wireline. Pumped inhibited 20% NEFE back rods off. Ba Picked up short si 12-5-96 - Picked u tubing and worked Left 82 rods in tu 12-6-96 - Strip ou rods and pump. Pa	and rigged up pulling w Rods are dragging bot g side tubing. s on short side. Would 1.825" F profile nipple 50 bbls of hot water dow cacid with paraffin disp tcked off 1 rod from surf de of tubing. Did not m up on long side tubing wi free. Picked up on rods bing. Started laying do it of hole with 92 joints trallel anchor stinger was s is rue sait complete to the best of my boowledge a Multiple of the set of my boowledge a	nit. Try to un h ways. Feels not come loose. on long side of m annulus follow ersent followed ace. Nippled d nove tubing. th 60K of tensis and rods were own 2-3/8" tubin s of 2-3/8" tubin as not on bottom mobelief.	seat pump on short side. Could m like short side tubing may be Rigged up wireline. TIH and se tubing at 8494'. Rigged down wed by 2000 gallons double by 50 bbls of hot water. Try to own wellhead and installed BOP. on. Picked up on short side loose. TOOH and laid down rods. g off of short side. ng, perforated sub, seating nipp of tubing. Picked up long CONTINUED ON NEXT PAGE: Technician DATE Dec. 13, 1996
work) SEE RULE 1103. 12-3-96 - Moved in get pump to unseat wrapped around lon 12-4-96 - Work rod standing valve in wireline. Pumped inhibited 20% NEFE back rods off. Ba Picked up short si 12-5-96 - Picked u tubing and worked Left 82 rods in tu 12-6-96 - Strip ou rods and pump. Pa I hereby certify that the information above SKONATURE TYPE OR FRINT NAME Rusty KI	and rigged up pulling wa Rods are dragging bot g side tubing. s on short side. Would 1.825" F profile nipple 50 bbls of hot water dow acid with paraffin disp teked off 1 rod from surf de of tubing. Did not m up on long side tubing wi free. Picked up on rods bing. Started laying do it of hole with 92 joints trallel anchor stinger wa is rue set complete to the best of my knowledge a lein	nit. Try to un h ways. Feels not come loose. on long side of on annulus followed face. Nippled d nove tubing. th 60K of tensis and rods were own 2-3/8" tubin s of 2-3/8" tubin s not on bottom mabelie. mmg Operations	seat pump on short side. Could n like short side tubing may be Rigged up wireline. TIH and set tubing at 8494'. Rigged down wed by 2000 gallons double by 50 bbls of hot water. Try to own wellhead and installed BOP. on. Picked up on short side loose. TOOH and laid down rods. g off of short side. ng, perforated sub, seating nipp of tubing. Picked up long CONTINUED ON NEXT PAGE: Technician DATE Dec. 13, 1996 TELEPHONE NO. 505/748-1
work) SEE RULE 1103. 12-3-96 - Moved in get pump to unseat wrapped around lon 12-4-96 - Work rod standing valve in wireline. Pumped inhibited 20% NEFE back rods off. Ba Picked up short si 12-5-96 - Picked u tubing and worked Left 82 rods in tu 12-6-96 - Strip ou rods and pump. Pa Ihereby certify that the information above SHONATURE TYPE OR FRINT NAME Rusty KI	and rigged up pulling wa Rods are dragging bot g side tubing. s on short side. Would 1.825" F profile nipple 50 bbls of hot water dow acid with paraffin disp teked off 1 rod from surf de of tubing. Did not m up on long side tubing wi free. Picked up on rods bing. Started laying do it of hole with 92 joints trallel anchor stinger wa is rue set complete to the best of my knowledge a lein	nit. Try to un h ways. Feels not come loose. on long side of on annulus followed face. Nippled d nove tubing. th 60K of tensis and rods were own 2-3/8" tubin s of 2-3/8" tubin s not on bottom mabelie. mmg Operations	seat pump on short side. Could r like short side tubing may be Rigged up wireline. TIH and se tubing at 8494'. Rigged down wed by 2000 gallons double by 50 bbls of hot water. Try to own wellhead and installed BOP. on. Picked up on short side loose. TOOH and laid down rods. g off of short side. ng, perforated sub, seating nipp of tubing. Picked up long CONTINUED ON NEXT PAGE: Technician DATE Dec. 13, 1996 TELEPHONE NO. 505/748-1
work) SEE RULE 1103. 12-3-96 - Moved in get pump to unseat wrapped around lon 12-4-96 - Work rod standing valve in wireline. Pumped inhibited 20% NEFE back rods off. Ba Picked up short si 12-5-96 - Picked u tubing and worked Left 82 rods in tu 12-6-96 - Strip ou rods and pump. Pa I hereby certify that the information above SHONATURE TYPE OR FRINT NAME Rusty KI	and rigged up pulling wa Rods are dragging bot g side tubing. s on short side. Would 1.825" F profile nipple 50 bbls of hot water dow acid with paraffin disp teked off 1 rod from surf de of tubing. Did not m up on long side tubing wi free. Picked up on rods bing. Started laying do it of hole with 92 joints trallel anchor stinger wa is rue set complete to the best of my knowledge a lein	nit. Try to un h ways. Feels not come loose. on long side of on annulus followed face. Nippled d nove tubing. th 60K of tensis and rods were own 2-3/8" tubin s of 2-3/8" tubin s not on bottom mabelie. mmg Operations	seat pump on short side. Could r like short side tubing may be Rigged up wireline. TIH and se tubing at 8494'. Rigged down wed by 2000 gallons double by 50 bbls of hot water. Try to own wellhead and installed BOP. on. Picked up on short side loose. TOOH and laid down rods. g off of short side. ng, perforated sub, seating nipp of tubing. Picked up long CONTINUED ON NEXT PAGE: Technician DATE Dec. 13, 1996 TELEPHONE NO. 505/748-1