

## FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Nearburg Producing Co.</u>		Lease <u>Morris Area 26F</u>		Well # <u>1</u>	
Location of Well	Unit <u>F</u>	Section <u>26</u>	Township <u>19</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	<u>United Drilling Inc.</u>		Type of Equipment <u>Rotary</u>		
* Witness <u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/4</u>	* <u>8 5/8</u>	<u>24 #</u>		<u>1100</u>	<u>650 Circ</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>15.50 #</u>		<u>4000</u>	<u>450 Tie</u>
					<u>into surf. csg.</u>
Casing Data:					
Surface <u>5</u> joints of <u>8 5/8</u> inch <u>24</u> # Grade <u>J-55</u>					
<u>(Approved)</u> (Rejected)					
Inspected by <u>Darrell Moore</u> date <u>6/3/89</u>					
Cementing Program					
Size of hole <u>12 1/4</u> Size of Casing <u>8 5/8</u> Sacks cement required <u>975 sks</u>					
Type of Shoe used _____ Float collar used <u>Yes</u> Btm 3 jts welded <u>Yes</u>					
TD of hole <u>1100</u> Set <u>1100</u> Feet of <u>8 5/8</u> Inch <u>24</u> # Grade <u>J-55</u>					
<u>(New)</u> -used csg. @ <u>1100'</u> with <u>975</u> sacks neat cement around shoe					
+ _____ sac additives _____					
Plug down @ <u>8:30 pm</u> (AM) <u>(PM)</u> Date <u>6/3/89</u>					
Cement circulated <u>Yes</u> No. of Sacks <u>280 sks</u>					
Cemented by <u>Haliborton</u> Witnessed by <u>Darrell Moore</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					