

DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

STANDARD IN TRIPLICATE  
(Other instructions on reverse side)

Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL

NM-24160

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Osage Federal

9. WELL NO.

10

10. FIELD AND POOL OR WILDCAT

Und. Bone Spring

11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA

Sec. 34: T19S, R29E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation. Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

NOV 1- '89

C. C. D. TESA OFFICE

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Siete Oil and Gas Corporation

3. ADDRESS OF OPERATOR

P.O. Box 2523

Roswell, NM 88202-2523

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface 1980' FNL & 660' FEL, SE $\frac{1}{4}$ NE $\frac{1}{4}$ , Unit Letter H

14. PERMIT NO

30-015-26178

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3310' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Spud, 20", 13 3/8" & 8 5/8" ☒

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

9/15/89 WEK Rig #2 spudded 26" hole @ 11:00 AM, lost returns @ 80'.  
9/16/89 TD 26" hole to 347' @ 12:30 AM, RU & ran 9 jts (350') 94# J-55 20" csg, set @ 347' w/260 sxs 35/65 POZA w/6% D-20,  $\frac{1}{4}$ # D-29 & 3% CaCl, tail-in w/250 sxs HEII w/3% CaCl &  $\frac{1}{4}$ # D-29, 1" to surface. PD @ 11:00 AM, WOC.  
9/18/89 TD 17 1/2" hole to 1150' @ 7:30 PMon 9/17/89, RU & ran 30 jts (1152') 13 3/8" 48#, 54.5# & 61# J-55 csg, set @ 1150' w/500 sxs 35/65 POZA w/6% D-20,  $\frac{1}{4}$ # D-29, 10% D-44 & 3% CaCl, tail-in w/250 sxs HEII w/ $\frac{1}{4}$ # D-29 & 3% CaCl, circ 40 sxs to pits, PD @ 6:45 AM, WOC.  
9/22/89 TD 12 1/4" hole to 3200' @ 7:30 AM, RU & ran 74 jts ( 3220.01') 24# & 32# 8 5/8" J-55 csg, set @ 3200' w/925 sxs 35/65 POZA w/6% D-20,  $\frac{1}{4}$ # D-29, 3% CaCl & (10# D-44 in 1st 175 sxs), tail-in w/250 sxs HEII w/ $\frac{1}{4}$ # D-29 & 3% CaCl, did not circ, PD @ 4:45 PM, pump 40 bbls sweep, spot 100 bbls on bottom, ran temp survey, set 50 sxs plugs @ 1781' & 1765' through 1", WOC & resume drlg.

*For Record only*

18. I hereby certify that the foregoing is true and correct

SIGNED

*Cathy Batley*

TITLE Drlg. & Prod. Tech.

DATE 10/31/89

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side