Form 3160-5		D STATES	ONTACT RECEIVIN OFFICE FOR NUME OF COPIES REDUIRED (Other_Instructions on re-	MM Roswell District C151 Modified Form No. NMO60-3160-4
(July 1989) (Formerly 9–331)		T OF THE INTER	IUR verse side) REGEL	5. LEASE DESIGNATION AND BERIAL NO.
		LAND MANAGEMEN		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
(Do not use this	IDRY NOTICES	AND REPORTS (drill or to deepen or plug	DN WELLS back to a different reservoir. roposals.)	N/A
	Use "APPLICATION	FOR PERMIT-" for such p	roposals.)	7. UNTLAGREEMENT NAME
1. OIL GAS WELL WELL	OTHER		1 m.	N/A.
2. NAME OF OPERATOR			3a. Area Code & Phone No. 505/748-1471	8. FARM OR LEASE NAME
YATES PETROLE	UM CORPORATION	/	RECEIVED	Allison CQ Federal 9. WBLL NO.
105 South 4th	St., Artesia,	NM 88210	,	10
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements." '90 See also space 17 below.)				10. FIELD AND POOL, OR WILDCAT
At surface		Sec. 13-T19S-R24	-	No. Dagger Draw Upper Penn 11. SBC., T., R., M., OB BLK. AND
1900 FN	L & OOU FEL,	Sec. 15-1155 R24	A second s	SURVEY OR ARMA
			ARTESIA, OFFICE	Unit H, Sec. 13-19S-24E
14. PERMIT NO.	i	ELEVATIONS (Show whether D	r, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE Eddy NM
API #30-015-261		3616' GR		
16.	Check Approp	riate Box To Indicate N	Nature of Notice, Report, or C	
	NOTICE OF INTENTION T	ov : ر	NUBSEQU	JENT REPORT OF:
TEST WATER SHUT-		DR ALTER CASING	WATER SHUT-OFF X.	ALTERING CASING
FRACTURE TREAT Shoot or acidize	ABAND	PLE COMPLETE	SHOOTING OR ACIDIZING	ABANDONMENT [®]
REPAIR WELL CHANGE PLANS (Other)				
(Other)			Completion or Recompl	of multiple completion on Well letion Report and Log form.)
proposed work. I nent to this work.)	f well is directionally	drilled, give subsurface loca	tions and mensured and true vertice	including estimated date of starting any al depths for all markers and zones perti-
MM of coud	Recumed drill.	ing 14-3/4" hole	6:30 PM 2-13-90. Not:	pipe. Notified BLM, Carlsbad
Carlsbad, NM. circulation 30 insert float s Gilsonite, 1/2 CaCl2 (yield 1 Cement did not cement 170'. Tag cement 135 sacks. WOC. 26 hrs. Reduc	2'. Ran 27 set 1168'. Cer #/sx Floseal a .32, wt 14.8) c circulate. N Spot 35 sx Cla 5'. Spot 250 s NU and tested and hole to 8-3 om Dale Armstry	joints 9-5/8" 36# mented w/1000 gals and 3% CaCl2 (yie . PD 9:00 PM 2- WOC 6 hrs. Ran t ass C Neat w/4% C sx Class C Neat w d to 1000 psi for 3/4". Drilled plu ong. BLM, Carlsba	nd pump LCM sweep, got J-55 casing set 1210 Flocheck II, 1100 sx 1d 1.8. wt 12.6). Fol. 15-90. Bumped plug to emp survey and found f aC12. PD 5:45 AM 2- /2% CaC12. PD 8:36 AM 30 mintues. Drilled g and resumed drilling d, NM to use Flocheck One-inching witnessed	t circulation back. Lost '. Guide shoe set 1210', Halliburton Lite w/10#/sx lowed w/200 sx Class C w/2% o 1000 psi, float held okay. TOC 180'. Ran 1". Tag 16-90. WOC 2 hrs. Ran 1". M 2-16-90. Circulated 20 out 11:00 PM 2-16-90. WOC g. NOTE: Received verbal II before cement. Set cemer d by Dale Carpenter, BLM,
Carlsbad, NM. circulation 30 insert float s Gilsonite, 1/2 CaCl2 (yield 1 Cement did not cement 170'. Tag cement 135 sacks. WOC. 26 hrs. Reduc permission fro basket on join	2'. Ran 27 set 1168'. Cer #/sx Floseal a .32, wt 14.8) c circulate. N Spot 35 sx Cla 5'. Spot 250 s NU and tested and hole to 8-3 om Dale Armstry	joints 9-5/8" 36# mented w/1000 gals and 3% CaCl2 (yie . PD 9:00 PM 2- WOC 6 hrs. Ran t ass C Neat w/4% C sx Class C Neat w d to 1000 psi for 3/4". Drilled plu ong. BLM, Carlsba	nd pump LCM sweep, got J-55 casing set 1210 Flocheck II, 1100 sx 1d 1.8. wt 12.6). Fol. 15-90. Bumped plug to emp survey and found f aC12. PD 5:45 AM 2- /2% CaC12. PD 8:36 AM 30 mintues. Drilled g and resumed drilling d, NM to use Flocheck One-inching witnessed	t circulation back. Lost '. Guide shoe set 1210', Halliburton Lite w/10#/sx lowed w/200 sx Class C w/2% o 1000 psi, float held okay. TOC 180'. Ran 1". Tag 16-90. WOC 2 hrs. Ran 1". M 2-16-90. Circulated 20 out 11:00 PM 2-16-90. WOC g. NOTE: Received verbal II before cement. Set cemen
Carlsbad, NM. circulation 30 insert float s Gilsonite, 1/2 CaCl2 (yield 1 Cement did not cement 170'. Tag cement 135 sacks. WOC. 26 hrs. Reduc permission fro basket on join	2'. Ran 27 set 1168'. Cer #/sx Floseal a .32, wt 14.8) c circulate. N Spot 35 sx Cla 5'. Spot 250 s NU and tested and hole to 8-3 om Dale Armstry	joints 9-5/8" 36# mented w/1000 gals and 3% CaCl2 (yie . PD 9:00 PM 2- WOC 6 hrs. Ran t ass C Neat w/4% C sx Class C Neat w d to 1000 psi for 3/4". Drilled plu ong. BLM, Carlsba	nd pump LCM sweep, god J-55 casing set 1210 Flocheck II, 1100 sx 1d 1.8. wt 12.6). Fol: 15-90. Bumped plug to emp survey and found 5 aC12. PD 5:45 AM 2- /2% CaC12. PD 8:36 AM 30 mintues. Drilled g and resumed drilling d, NM to use Flocheck One-inching witnessed ACCEPTED	t circulation back. Lost '. Guide shoe set 1210', Halliburton Lite w/10#/sx lowed w/200 sx Class C w/2% o 1000 psi, float held okay. TOC 180'. Ran 1". Tag 16-90. WOC 2 hrs. Ran 1". M 2-16-90. Circulated 20 out 11:00 PM 2-16-90. WOC g. NOTE: Received verbal II before cement. Set cemen d by Dale Carpenter, BLM,
Carlsbad, NM. circulation 30 insert float s Gilsonite, 1/2 CaCl2 (yield 1 Cement did not cement 170'. Tag cement 135 sacks. WOC. 26 hrs. Reduc permission fro basket on joir Carlsbad, NM.	2'. Ran 27 set 1168'. Cer 2#/sx Floseal a .32, wt 14.8) circulate. N Spot 35 sx Cla 5'. Spot 250 NU and tester ced hole to 8- om Dale Armstronts #15 (520')	joints 9-5/8" 36# mented w/1000 gals and 3% CaCl2 (yie . PD 9:00 PM 2- WOC 6 hrs. Ran t ass C Neat w/4% C sx Class C Neat w d to 1000 psi for 3/4". Drilled plu ong, BLM, Carlsba and #19 (313').	nd pump LCM sweep, got J-55 casing set 1210 Flocheck II, 1100 sx 1d 1.8. wt 12.6). Fol: 15-90. Bumped plug to emp survey and found 7 aC12. PD 5:45 AM 2-1 /2% CaC12. PD 8:36 AN 30 mintues. Drilled g and resumed drilling d, NM to use Flocheck One-inching witnessed ACCEPTED Acto MAR	t circulation back. Lost '. Guide shoe set 1210', Halliburton Lite w/10#/sx lowed w/200 sx Class C w/2% o 1000 psi, float held okay. TOC 180'. Ran 1". Tag 16-90. WOC 2 hrs. Ran 1". M 2-16-90. Circulated 20 out 11:00 PM 2-16-90. WOC g. NOTE: Received verbal II before cement. Set cemen d by Dale Carpenter, BLM, O FOR RECORD
Carlsbad, NM. circulation 30 insert float s Gilsonite, 1/2 CaCl2 (yield 1 Cement did not cement 170'. Tag cement 135 sacks. WOC. 26 hrs. Reduc permission fro basket on join	2'. Ran 27 set 1168'. Cer 2#/sx Floseal a .32, wt 14.8) circulate. N Spot 35 sx Cla 5'. Spot 250 NU and tester ced hole to 8- om Dale Armstronts #15 (520')	joints 9-5/8" 36# mented w/1000 gals and 3% CaCl2 (yie . PD 9:00 PM 2- WOC 6 hrs. Ran t ass C Neat w/4% C sx Class C Neat w d to 1000 psi for 3/4". Drilled plu ong, BLM, Carlsba and #19 (313').	nd pump LCM sweep, got J-55 casing set 1210 Flocheck II, 1100 sx 1d 1.8. wt 12.6). Fol: 15-90. Bumped plug to emp survey and found 7 aC12. PD 5:45 AM 2-1 /2% CaC12. PD 8:36 AN 30 mintues. Drilled g and resumed drilling d, NM to use Flocheck One-inching witnessed ACCEPTED Acto MAR	t circulation back. Lost '. Guide shoe set 1210', Halliburton Lite w/10#/sx lowed w/200 sx Class C w/2% o 1000 psi, float held okay. TOC 180'. Ran 1". Tag 16-90. WOC 2 hrs. Ran 1". M 2-16-90. Circulated 20 out 11:00 PM 2-16-90. WOC g. NOTE: Received verbal II before cement. Set cemen d by Dale Carpenter, BLM, FOR RECORD
Carlsbad, NM. circulation 30 insert float s Gilsonite, 1/2 CaCl2 (yield I Cement did not cement 170'. Tag cement 135 sacks. WOC. 26 hrs. Reduc permission fro basket on join Carlsbad, NM.	2'. Ran 27 set 1168'. Cer 2#/sx Floseal a .32, wt 14.8) circulate. N Spot 35 sx Cla 5'. Spot 250 NU and tester ced hole to 8- om Dale Armstronts #15 (520')	joints 9-5/8" 36# mented w/1000 gals and 3% CaCl2 (yie . PD 9:00 PM 2- WOC 6 hrs. Ran t ass C Neat w/4% C sx Class C Neat w d to 1000 psi for 3/4". Drilled plu ong, BLM, Carlsba and #19 (313').	nd pump LCM sweep, got J-55 casing set 1210 Flocheck II, 1100 sx 1d 1.8. wt 12.6). Fol: 15-90. Bumped plug to emp survey and found f aC12. PD 5:45 AM 2- /2% CaC12. PD 8:36 AN 30 mintues. Drilled g and resumed drilling d, NM to use Flocheck One-inching witnessed ACCEPTED Acc MAR MAR	<pre>t circulation back. Lost '. Guide shoe set 1210', Halliburton Lite w/10#/sx lowed w/200 sx Class C w/2% o 1000 psi, float held okay. TOC 180'. Ran 1". Tag 16-90. WOC 2 hrs. Ran 1". M 2-16-90. Circulated 20 out 11:00 PM 2-16-90. WOC g. NOTE: Received verbal II before cement. Set cemen d by Dale Carpenter, BLM, O FOR RECORD A 14 1990 A 14 1990 A 1</pre>

*See Instructions on Reverse Side