

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NEW OIL COND. COMMISSION
Draper LD
Artesia, N.M. 88210
SUMMIT IN TRIPPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Fred Pool Drilling, Inc.

3. ADDRESS OF OPERATOR
P.O. Box 1393, Roswell, N.M. 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

14. PERMIT NO.
30-015-26222

15. ELEVATIONS (Show whether DF, RT, OR, etc.)
3321' GR

RECEIVED
DEC 18 '89
O. C. D.
ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.
NM 58815

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
RONADERO FEDERAL

9. WELL NO.
2

10. FIELD AND POOL, OR WILDCAT
Und. Turkey Trk. SR-O-G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 31-T19S-R30E

12. COUNTY OR PARISH
Fddy

13. STATE
N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)	☐	WATER SHUT-OFF	☐
		FRACTURE TREATMENT	☐
		SHOOTING OR ACIDIZING	☐
		(Other) casing	☐
		REPAIRING WELL	☐
		ALTERING CASING	☐
		ABANDONMENT*	☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

December 4, 1989: TD 8500 ft.
December 4, 1989: Plugged back to 6645' and set production casing as follows:
Set 35sx plug at 8484'. Pulled up to 6751' and set 35 sx cement, WOC 2hrs. Did not get a tag, set another plug with 35 sx at 6751'. WOC 3hrs, then tagged at 6645'. (Plug back procedure as per verbal order from Shannon Shaw, BLM.)
All plugs are Class "H", 2% CaCl. Drilling mud between plugs.

December 5, 1989: Ran 6642' of 4½ used, 11.60# LTC casing, N-80. Cemented with 675 sx 50/50 POZ. Plug on bottom at 1:00 p.m.

Intend to perforate and acidize well.

18. I hereby certify that the foregoing is true and correct

SIGNED

Santa Groal

TITLE

Vice President

DATE

12-12-89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: